

GENSET MODEL		7		
Model	MG	TP 100 SS FI		
Mechanical version	Silenced v steel shee canopy,co	Silenced version with galvanized steel sheet and powder-painted canopy, compact baseframe, with bunded tank and leak control		
Fuel Tank Capacity	lt.	160		
Rated technical data				
Prime Power (PRP)	kVA	100		
Prime Power (PRP)	KW	80		
Limited Power (LTP)	kVA	110		
Limited Power (LTP)	KW	88		
Rated Power Factor (cosφ)		0.8		
Windings		Three phases Series Star		
Rated three-phase concatenated Voltage	V	400		
Rated phase-neutral voltage	V	230		
Rated frequency	Hz	50		
Fuel type		Diesel		
Dimensions And Noise				
Length	mm	2560		
Width	mm	1040		
Height	mm	1805		
Weight	Kg	1600		
Sound pressure 7 m.	dBA	65		
Fuel consumption				
Fuel Cons. at 100% (LTP)	l/h	24,4		
Fuel Cons. at 100% (PRP)	l/h	22		
Fuel Cons. at 75% (PRP)	l/h	15,3		
Fuel Cons. at 50% (PRP)	l/h	11		
General Alternator Data				
Alternator brand		STAMFORD		
Alternator model		UCI274C		
PRP Power	kVA	100		
LTP Power	kVA	110		
Winding		Three phases Series Star		
Terminals Number		12 nr		
IP Protection		23		
Electronic regulator		SX460		
Precision		± 1.50 %		
The company reserves the right to more	lify the technic	ral specifications items		

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.



General Engine Data			
Engine brand		FPT IVECO	
Engine model		N45TM2A	
Cylinders		4	
R.P.M.		1500	
Cubic capacity		4500	
Air intake		Turbo	
Standard voltage	Vdc	12	
Sae		-	
BMEP	kPa	1584	
Cooling		Water	
Flywheel P.R.P. Power	kW	87,5	
Flywheel Stand-by Power	kW	96,2	
Electronic regulator		On request	
Precision class		G2	
Oil quantity	lt.	12,8	
EU Stage		STAGE 2	

Standard Features

Hard wires connection protected

Electrical panel DSE 4520 mounted on board with safety cover Circuit breaker

Internal exhaust gas silencer and insulated manifold

Engine oil extraction pump and fuel decanter filter

12V Battery with battery switch

Bunded tank

Lifting hooks and side forklift pockets

Options factory installed

220V Electric pre-heater

KIT socket TPS01: 1x32A, 1x16A 3Ph

1x16A 1Ph + 1x16A Schuko

1x63A, 1x32A, 1x16A 3Ph

KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko

125A breaker with adj. earth fault relay

Kit AMF and ATS panel

Predisposition for quick release fitting for external fuel tank

Oversize fuel tank

