

GENSET MODEL			
Model	MGTP 170 SS FI		
Mechanical version	Silenced version with galvanized steel sheet and powder-painted canopy, compact baseframe, with bunded tank and leak control		
Fuel Tank Capacity	lt.	360	
Rated technical data			
Prime Power (PRP)	kVA	174	
Prime Power (PRP)	KW	139,2	
Limited Power (LTP)	kVA	191	
Limited Power (LTP)	KW	152,8	
Rated Power Factor (cosφ)		0.8	
Windings		Three phases Series Star	
Rated three-phase concatenated Voltage	V	400	
Rated phase-neutral voltage	V	230	
Rated frequency	Hz	50	
Fuel type		Diesel	
Dimensions And Noise			
Length	mm	3060	
Width	mm	1140	
Height	mm	2230	
Weight	Kg	2050	
Sound pressure 7 m.	dBA	68	
Fuel consumption			
Fuel Cons. at 100% (LTP)	l/h	42,2	
Fuel Cons. at 100% (PRP)	l/h	36,6	
Fuel Cons. at 75% (PRP)	l/h	27,5	
Fuel Cons. at 50% (PRP)	I/h	18	
General Alternator Data	1/11	10	
Alternator brand		STAMFORD	
Alternator model		UCI274G	
PRP Power	kVA	180	
LTP Power	kVA	194	
Winding		Three phases Series Star	
Terminals Number		12 nr	
IP Protection		23	
Electronic regulator		SX460	
Precision		± 1.50 %	
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		A 7) 2m	

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.



1	General Engine Data		
	Engine brand		FPT IVECO
	Engine model		N67TM4
	Cylinders		6
	R.P.M.		1500
	Cubic capacity		6700
	Air intake		Turbo
	Standard voltage	Vdc	12
	Sae		-
	BMEP	kPa	1850
	Cooling		Water
	Flywheel P.R.P. Power	kW	149,7
	Flywheel Stand-by Power	kW	165
	Electronic regulator		On request
	Precision class		G3
	Oil quantity	lt.	17,2
	EU Stage		Not available

Standard Features

Hard wires connection protected

 $Electrical\ panel\ Com Ap\ AMF25\ mounted\ on\ board\ with\ safety\ cover$

Circuit breaker

Internal exhaust gas silencer and insulated manifold

Engine oil extraction pump and fuel decanter filter

12V Battery with battery switch

Bunded tank

Lifting hooks and side forklift pockets

Options factory installed

220V Electric pre-heater

KIT socket TPS01: 1x32A, 1x16A 3Ph

1x16A 1Ph + 1x16A Schuko

1x63A, 1x32A, 1x16A 3Ph

KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko

125A breaker with adj. earth fault relay

Kit AMF and ATS panel

 $Predisposition \ for \ quick \ release \ fitting \ for \ external \ fuel \ tank$

Oversize fuel tank

