Serkins

UARE	7/K94I	
GENSET MODEL		
Model	MG	TP 180 SS PI
Mechanical version	Silenced version with galvanized steel sheet and powder-painted canopy, compact baseframe, with bunded tank and leak control	
Fuel Tank Capacity	lt.	360
Rated technical data		
Prime Power (PRP)	kVA	180
Prime Power (PRP)	KW	144
Limited Power (LTP)	kVA	194
Limited Power (LTP)	KW	155,2
Rated Power Factor (cosφ)		0.8
Windings		Three phases Series Star
Rated three-phase concatenated Voltage	V	400
Rated phase-neutral voltage	V	230
Rated frequency	Hz	50
Fuel type		Diesel
Dimensions And Noise		
Length	mm	3060
Width	mm	1140
Height	mm	2230
Weight	Kg	2380
Sound pressure 7 m.	dBA	72
Fuel consumption		
Fuel Cons. at 100% (LTP)	l/h	45,1
Fuel Cons. at 100% (PRP)	l/h	41,4
Fuel Cons. at 75% (PRP)	l/h	32
Fuel Cons. at 50% (PRP)	l/h	20,2
General Alternator Data		
Alternator brand		STAMFORD
Alternator model		UCI274G
PRP Power	kVA	180
LTP Power	kVA	194
Winding		Three phases Series Star
Terminals Number		12 nr.
IP Protection		23
Electronic regulator		SX460
Precision		± 1.50 %
The	156 . 16 . 1 . 1 . 1 . 1 . 1 . 1 . 1 . 1 .	一

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.



General Engine Data		
Engine brand		PERKINS
Engine model		1106A-70TAG3
Cylinders		6
R.P.M.		1500
Cubic capacity		7010
Air intake		Turbo
Standard voltage	Vdc	12
Sae		-
ВМЕР	kPa	1857
Cooling		Water
Flywheel P.R.P. Power	kW	157,7
Flywheel Stand-by Power	kW	175,2
Electronic regulator		On request
Precision class		G2
Oil quantity	lt.	16,5
EU Stage		Not available
Standard Features		
Hard wires connection protected		

Hard wires connection protected

Electrical panel ComAp AMF25 mounted on board with safety cover Circuit breaker

Internal exhaust gas silencer and insulated manifold Engine oil extraction pump and fuel decanter filter

12V Battery with battery switch

Bunded tank

Lifting hooks and side forklift pockets

Options factory installed

220V Electric pre-heater

1x32A, 1x16A 3Ph KIT socket TPS01:

1x16A 1Ph + 1x16A Schuko

1x63A, 1x32A, 1x16A 3Ph

KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko

125A breaker with adj. earth fault relay

Kit AMF and ATS panel

Predisposition for quick release fitting for external fuel tank

Oversize fuel tank

