INDUSTRIAL LINE

MGTP 250 SS PI

BPerkins[®]

GENSET MODEL		
Model	MG	TP 250 SS PI
Model		version with galvanized
		et and powder-painted
Mechanical version	canopy, compact base frame, with	
		ank and leak control
Fuel Tank Capacity	lt.	360
Rated technical data	1.5.76	
Prime Power (PRP)	kVA	250
Prime Power (PRP)	KW	200
Limited Power (LTP)	kVA	275
Limited Power (LTP)	KW	220
Rated Power Factor (cosφ)		0.8
Windings		Three phases
-		Series Star
Rated three-phase	V	400
concatenated Voltage		
Rated phase-neutral voltage	V	230
Rated frequency	Hz	50
Fuel type		Diesel
Dimensions And Noise		
Length	mm	3230
Width	mm	1140
Height	mm	2250
Weight	Kg	2860
Sound pressure 7 m.	dBA	78
Fuel consumption		
Fuel Cons. at 100% (LTP)	l/h	60,7
Fuel Cons. at 100% (PRP)	l/h	55,5
Fuel Cons. at 75% (PRP)	l/h	41,6
Fuel Cons. at 50% (PRP)	l/h	28,9
General Alternator Data		
Alternator brand		STAMFORD
Alternator model		UCDI274K
PRP Power	kVA	250
_TP Power	kVA	275
		Three phases
Winding		Series Star
Terminals Number		12 nr.
P Protection		23
		SX460
Electronic regulator		JATUU
Electronic regulator Precision		± 1.50 %





General Engine Da	ita				
Engine brand			PERKINS		
Engine model			1506A-E88TAG3		
Cylinders			6		
R.P.M.			1500		
Cubic capacity			8800		
Air intake			Turbo		
Standard voltage		Vdc	24		
Sae			-		
BMEP		kPa	2145		
Cooling			Water		
Flywheel P.R.P. Pov	ver	kW	222		
Flywheel Stand-by	/ Power	kW	244		
Electronic regulate	or		Standard		
Precision class			G2		
Oil quantity		lt.	41		
EU Stage			Not available		
Standard Features					
Hard wires connection protected					
Electrical panel ComAp AMF25 mounted on board with safety cover					
Circuit breaker					
Internal exhaust gas silencer and insulated manifold					
Engine oil extraction pump and fuel decanter filter					
12V Battery with battery switch					
Bunded tank					
Lifting hooks and side forklift pockets					
Options factory installed					
220V Electric pre-heater					
KIT socket TPS01:	1x32A, 1x16A 3Ph 1x16A 1Ph + 1x16A Schuko				
1x63A, 1x32A, 1x16A 3Ph KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko 125A breaker with adj. earth fault relay					
Kit AMF and ATS panel					
Predisposition for quick release fitting for external fuel tank					
Oversize fuel tank					

Trime UK Limited | B3 Spitfire Close, Huntingdon, Cambridgeshire PE29 6XY 01480 220500 | www.trimeuk.com | sales@trimeuk.com