INDUSTRIAL LINE

MGTP 40 SS PI

BPerkins[®]

GENSET MODEL Model

Mechanical version

MGTP 40 SS PI

Silenced version with galvanized steel sheet and powder-painted canopy, compact baseframe, with bunded tank and leak control

Fuel Tank Capacity	lt.	160
Rated technical data		
Prime Power (PRP)	kVA	40
Prime Power (PRP)	KW	32
Limited Power (LTP)	kVA	44
Limited Power (LTP)	KW	35,2
Rated Power Factor (cosφ)		0.8
Windings		Three phases Series Star
Rated three-phase concatenated Voltage	V	400
Rated phase-neutral voltage	V	230
Rated frequency	Hz	50
Fuel type		Diesel
Dimensions And Noise		
Length	mm	2260
Width	mm	1040
Height	mm	1820
Weight	Kg	1240
Sound pressure 7 m.	dBA	61

Fuel consumption

ruciconsumption		
Fuel Cons. at 100% (LTP)	l/h	12
Fuel Cons. at 100% (PRP)	l/h	10,7
Fuel Cons. at 75% (PRP)	l/h	8,2
Fuel Cons. at 50% (PRP)	l/h	5,7
General Alternator Data		
Alternator brand		STAMFORD
Alternator model		S1L2-K
PRP Power	kVA	40
LTP Power	kVA	44
Winding		Three phases Series Star
Terminals Number		12 nr.
IP Protection		23
Electronic regulator		AS540
Precision		± 1.00 %

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.





	-10 ×	
General Engine Data		
Engine brand		PERKINS
Engine model		1103A-33TG1
Cylinders		3
R.P.M.		1500
Cubic capacity		3300
Air intake		Turbo
Standard voltage	Vdc	12
Sae		-
BMEP	kPa	1023
Cooling		Water
Flywheel P.R.P. Power	kW	41,3
Flywheel Stand-by Power	kW	45,6
Electronic regulator		On request
Precision class		G2
Oil quantity	lt.	8,3
EU Stage		Not available
Standard Features		

Hard wires connection protected

Electrical panel DSE 4520 mounted on board with safety cover Circuit breaker

Internal exhaust gas silencer and insulated manifold Engine oil extraction pump and fuel decanter filter

12V Battery with battery switch

Bunded tank

Lifting hooks and side forklift pockets

Options factory installed

220V Electric pre-heater

KIT socket TPS01:	KIT cocket TDC01.	1x32A, 1x16A 3Ph	
	1x16A 1Ph + 1x16A Schuko		
		1x63A, 1x32A, 1x16A 3Ph	
	KIT socket TPS03:	1x16A 1Ph + 1x16A Schuko	
		125A breaker with adj. earth fault relay	
Kit AMF and ATS panel			
	Predisposition for	quick release fitting for external fuel tank	

Predisposition for quick release fitting for external fuel tank Oversize fuel tank

Trime UK Limited | B3 Spitfire Close, Huntingdon, Cambridgeshire PE29 6XY 01480 220500 | www.trimeuk.com | sales@trimeuk.com