



GENSET MODEL

Model **MGTP 400 SS FI**

Mechanical version Silenced version with galvanized steel sheet and powder-painted canopy, compact baseframe, with bunded tank and leak control

Fuel Tank Capacity lt. 400

Rated technical data

Prime Power (PRP) kVA 400

Prime Power (PRP) KW 320

Limited Power (LTP) kVA 440

Limited Power (LTP) KW 352

Rated Power Factor (cosφ) 0.8

Windings Three phases Series Star

Rated three-phase concatenated Voltage V 400

Rated phase-neutral voltage V 230

Rated frequency Hz 50

Fuel type Diesel

Dimensions And Noise

Length mm 4000

Width mm 1300

Height mm 2400

Weight Kg 4340

Sound pressure 7 m. dBA 72

Fuel consumption

Fuel Cons. at 100% (LTP) l/h 98,5

Fuel Cons. at 100% (PRP) l/h 87,5

Fuel Cons. at 75% (PRP) l/h 68

Fuel Cons. at 50% (PRP) l/h 48,6

General Alternator Data

Alternator brand STAMFORD

Alternator model S4L1D-F

PRP Power kVA 415

LTP Power kVA 465

Winding Three phases Series Star

Terminals Number 12 nr

IP Protection 23

Electronic regulator AS440

Precision ± 1.00 %

The company reserves the right to modify the technical specifications, items and design without notice.
The images of the products are indicative for illustrative purposes only.

General Engine Data

Engine brand FPT IVECO

Engine model C13TE3A

Cylinders 6

R.P.M. 1500

Cubic capacity 12900

Air intake Turbo

Standard voltage Vdc 24

Sae -

BMEP kPa 2259

Cooling Water

Flywheel P.R.P. Power kW 352

Flywheel Stand-by Power kW 387

Electronic regulator Standard

Precision class G2

Oil quantity lt. 35

EU Stage STAGE 2

Standard Features

- Hard wires connection protected
- Electrical panel ComAp AMF25 mounted on board with safety cover
- Circuit breaker
- Internal exhaust gas silencer and insulated manifold
- Engine oil extraction pump and fuel decanter filter
- 12V Battery with battery switch
- Bunded tank
- Lifting hooks and side forklift pockets

Options factory installed

- 220V Electric pre-heater
- KIT socket TPS01: 1x32A, 1x16A 3Ph
1x16A 1Ph + 1x16A Schuko
- 1x63A, 1x32A, 1x16A 3Ph
- KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko
125A breaker with adj. earth fault relay
- Kit AMF and ATS panel
- Predisposition for quick release fitting for external fuel tank
- Oversize fuel tank