INDUSTRIAL LINE

MGTP 400 SS PI

BPerkins[®]

MGTP 400 SS PI Silenced version with galvanized

GENSET MODEL

Model



General Engine Da	ta			
Engine brand			PERKINS	
Engine model			2206C-E13TAG3	
Cylinders			б	
R.P.M.			1500	
Cubic capacity			12500	
Air intake			Turbo	
Standard voltage		Vdc	24	
Sae			-	
BMEP		kPa	2345	
Cooling			Water	
Flywheel P.R.P. Power		kW	348,9	
Flywheel Stand-by Power		kW	392,3	
Electronic regulator			Standard	
Precision class			G2	
Oil quantity		lt.	40	
EU Stage			STAGE 2	
Standard Features				
Hard wires connec	tion protected			
Electrical panel ComAp AMF25 mounted on board with safety cove				
Circuit breaker				
Internal exhaust gas silencer and insulated manifold				
Engine oil extraction pump and fuel decanter filter				
12V Battery with battery switch				
Bunded tank				
Lifting hooks and s	side forklift pock	kets		
Options factory ins	stalled			
220V Electric pre-h	neater			
KIT socket TPS01:	1x32A, 1x16A 3 1x16A 1Ph + 1x		uko	
KIT socket TPS03:	1x63A, 1x32A, 1x16A 3Ph			
Kit AMF and ATS p		, i		
Predisposition for		ting for e	xternal fuel tank	
Oversize fuel tank		-		
	e NGA			

Mechanical version	steel shee canopy,co	steel sheet and powder-painted canopy,compactbaseframe,with bunded tank and leak control		
Fuel Tank Capacity	lt.	400		
Rated technical data				
Prime Power (PRP)	kVA	400		
Prime Power (PRP)	KW	320		
Limited Power (LTP)	kVA	450		
Limited Power (LTP)	KW	360		
Rated Power Factor (cosφ)		0.8		
Windings		Three phases Series Star		
Rated three-phase concatenated Voltage	V	400		
Rated phase-neutral voltage	V	230		
Rated frequency	Hz	50		
Fuel type		Diesel		
Dimensions And Noise				
Length	mm	4000		
Width	mm	1300		
Height	mm	2564		
Weight	Kg	4530		
Sound pressure 7 m.	dBA	72		
Fuel consumption				
Fuel Cons. at 100% (LTP)	l/h	94		
Fuel Cons. at 100% (PRP)	l/h	85		
Fuel Cons. at 75% (PRP)	l/h	65		
Fuel Cons. at 50% (PRP)	l/h	46		
General Alternator Data				
Alternator brand		STAMFORD		
Alternator model		S4L1D-F		
PRP Power	kVA	415		
LTP Power	kVA	465		
Winding		Three phases Series Star		
Terminals Number		12 nr.		
IP Protection		23		
Electronic regulator		AS440		
Precision		± 1.00 %		
The company reserves the right to modify the technical specifications, items and design without notice.				

The images of the products are indicative for illustrative purposes only.



Trime UK Limited | B3 Spitfire Close, Huntingdon, Cambridgeshire PE29 6XY 01480 220500 | www.trimeuk.com | sales@trimeuk.com