Serkins

	TO A		
GENSET MODEL			
Model	MGTP 500 SS PI		
Mechanical version	steel shee	Silenced version with galvanized steel sheet and powder-painted canopy, compact baseframe, with bunded tank and leak control	
Fuel Tank Capacity	lt.	950	
Rated technical data			
Prime Power (PRP)	kVA	500	
Prime Power (PRP)	KW	400	
Limited Power (LTP)	kVA	520	
Limited Power (LTP)	KW	416	
Rated Power Factor (cosφ)		0.8	
Windings		Three phases Series Star	
Rated three-phase concatenated Voltage	V	400	
Rated phase-neutral voltage	V	230	
Rated frequency	Hz	50	
Fuel type		Diesel	
Dimensions And Noise			
Length	mm	4500	
Width	mm	1840	
Height	mm	2540	
Weight	Kg	5750	
Sound pressure 7 m.	dBA	73	
Fuel consumption			
Fuel Cons. at 100% (LTP)	l/h	114	
Fuel Cons. at 100% (PRP)	l/h	106	
Fuel Cons. at 75% (PRP)	l/h	81	
Fuel Cons. at 50% (PRP)	l/h	55	
General Alternator Data			
Alternator brand		STAMFORD	
Alternator model		HCI5C	
PRP Power	kVA	500	
LTP Power	kVA	520	
Winding		Three phases Series Star	
Terminals Number		12 nr.	
IP Protection		23	
Electronic regulator		AS440	
Precision		± 1.00 %	
The company reserves the right to mod	lify the techniq	cal specifications items	

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.



General Engine Data		
Engine brand		PERKINS
Engine model		2506C-E15TAG2
Cylinders		6
R.P.M.		1500
Cubic capacity		15200
Air intake		Turbo
Standard voltage	Vdc	24
Sae		-
BMEP	kPa	2405
Cooling		Water
Flywheel P.R.P. Power	kW	435
Flywheel Stand-by Power	kW	478
Electronic regulator		Standard
Precision class		G3
Oil quantity	lt.	62
EU Stage		STAGE 2
	Engine brand Engine model Cylinders R.P.M. Cubic capacity Air intake Standard voltage Sae BMEP Cooling Flywheel P.R.P. Power Flywheel Stand-by Power Electronic regulator Precision class Oil quantity	Engine brand Engine model Cylinders R.P.M. Cubic capacity Air intake Standard voltage Vdc Sae BMEP kPa Cooling Flywheel P.R.P. Power kW Flywheel Stand-by Power kW Electronic regulator Precision class Oil quantity It.

Standard Features

Hard wires connection protected

Electrical panel ComAp AMF25 mounted on board with safety cover Circuit breaker

Internal exhaust gas silencer and insulated manifold Engine oil extraction pump and fuel decanter filter

12V Battery with battery switch

Bunded tank

Lifting hooks and side forklift pockets

Options factory installed

220V Electric pre-heater

KIT socket TPS01: 1x32A, 1x16A 3Ph

1x16A 1Ph + 1x16A Schuko

1x63A, 1x32A, 1x16A 3Ph

KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko

125A breaker with adj. earth fault relay

Kit AMF and ATS panel

Predisposition for quick release fitting for external fuel tank

Oversize fuel tank

