INDUSTRIAL LINE

MGTP 60 SS PI

BPerkins[®]

GENSET MODEL Model

Mechanical version

MGTP 60 SS PI Silenced version with galvanized

steel sheet and powder-painted canopy, compact base frame, with bunded tank and leak control

Fuel Tank Capacity	lt.	160	
Rated technical data			X
Prime Power (PRP)	kVA	60	
Prime Power (PRP)	KW	48	X
Limited Power (LTP)	kVA	66	
Limited Power (LTP)	KW	52,8	
Rated Power Factor (cosφ)		0.8	
Windings		Three phases Series Star	IJ
Rated three-phase concatenated Voltage	V	400	
Rated phase-neutral voltage	V	230	
Rated frequency	Hz	50	
Fuel type		Diesel	
Dimensions And Noise			
Length	mm	2260	
Width	mm	1040	
Height	mm	1820	
Weight	Kg	1230	
Sound pressure 7 m.	dBA	60	
Fuel consumption			
Fuel Cons. at 100% (LTP)	l/h	15,9	
Fuel Cons. at 100% (PRP)	l/h	14,6	
Fuel Cons. at 75% (PRP)	l/h	10,8	
Fuel Cons. at 50% (PRP)	l/h	7,6	
General Alternator Data			
Alternator brand		STAMFORD	
Alternator model		S1L2-Y	
PRP Power	kVA	62,5	
LTP Power	kVA	68,8	
Winding		Three phases Series Star	
Terminals Number		12 nr.	
IP Protection		23	
Electronic regulator		AS540	5
Precision		± 1.00 %	
The company promises the night to provide		The New Groupster	

The company reserves the right to modify the technical specifications, items and design without notice.

General Engine Data				
Engine brand		PERKINS		
Engine model		1103A-33TG2		
Cylinders		3		
R.P.M.		1500		
Cubic capacity		3300		
Air intake		Turbo		
Standard voltage	Vdc	12		
Sae		-		
BMEP	kPa	1333		
Cooling		Water		
Flywheel P.R.P. Power	kW	53,8		
Flywheel Stand-by Power	kW	59,3		
Electronic regulator		On request		
Precision class		G2		
Oil quantity	lt.	8,3		
EU Stage		Not available		
Standard Features				
Hard wires connection protected				
Electrical panel DSE 4520 mounted on board with safety cover				
Circuit breaker				
Internal exhaust gas silencer and insulated manifold				

Internal exhaust gas silencer and insulated manifold Engine oil extraction pump and fuel decanter filter

12V Battery with battery switch

Bunded tank

Lifting hooks and side forklift pockets

Options factory installed

Oversize fuel tank

220V Electric pre-heater

KIT socket TPS01:	KIT cocket TDC01	1X32A, 1X10A 3PN	
	1x16A 1Ph + 1x16A Schuko		
	1x63A, 1x32A, 1x16A 3Ph		
	KIT socket TPS03:	1x16A 1Ph + 1x16A Schuko	
		125A breaker with adj. earth fault relay	
	Kit AMF and ATS panel		
Predisposition for quick release fitting for external fuel tar			

The images of the products are indicative for illustrative purposes only.

