INDUSTRIAL LINE

MGTP 600 SS PI

88 Perkins[®]

MGTP 600 SS PI

Silenced version with galvanized steel sheet and powder-painted



E E						
A K						
	General Engine Da	ita				
	Engine brand			PERKINS		
	Engine model			2806C-E18TAG1A		
A	Cylinders			6		
	R.P.M.			1500		
XUS	Cubic capacity			18130		
	Air intake			Turbo		
	Standard voltage		Vdc	24		
	Sae			-		
	BMEP		kPa	2347		
	Cooling			Water		
	Flywheel P.R.P. Pov	ver	kW	514		
_	Flywheel Stand-by	/ Power	kW	565		
	Electronic regulate	or		Standard		
	Precision class			G3		
	Oil quantity		lt.	62		
	EU Stage			STAGE 2		
	Standard Features					
	Hard wires connection protected					
	Electrical panel ComAp AMF25 mounted on board with safety cover					
	Circuit breaker					
	Internal exhaust gas silencer and insulated manifold					
	Engine oil extraction pump and fuel decanter filter					
_	12V Battery with battery switch					
	Bunded tank					
	Lifting hooks and side forklift pockets					
	Options factory installed					
	220V Electric pre-heater					
	KIT socket TPS01: 1x32A, 1x16A 3Ph 1x16A 1Ph + 1x16A Schuko					
	1x63A, 1x32A, 1x16A 3Ph KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko 125A breaker with adj. earth fault relay					
	Kit AMF and ATS panel					
ms	Predisposition for quick release fitting for external fuel tank					
	Oversize fuel tank					
		S NEV				

Mechanical version
Fuel Tank Capacity

GENSET MODEL

Model

Mechanical version	canopy, compact base frame, with				
	bunded t	ank and leak control			
Fuel Tank Capacity	lt.	950			
Rated technical data					
Prime Power (PRP)	kVA	600			
Prime Power (PRP)	KW	480			
Limited Power (LTP)	kVA	660			
Limited Power (LTP)	KW	528			
Rated Power Factor (cosq)		0.8			
Windings		Three phases Series Star			
Rated three-phase concatenated Voltage	V	400			
Rated phase-neutral voltage	V	230			
Rated frequency	Hz	50			
Fuel type		Diesel			
Dimensions And Noise					
Length	mm	4500			
Width	mm	1840			
Height	mm	2540			
Weight	Kg	5710			
Sound pressure 7 m.	dBA	74			
Fuel consumption					
Fuel Cons. at 100% (LTP)	l/h	134			
Fuel Cons. at 100% (PRP)	l/h	129			
Fuel Cons. at 75% (PRP)	l/h	96			
Fuel Cons. at 50% (PRP)	l/h	63			
General Alternator Data					
Alternator brand		STAMFORD			
Alternator model		HCI5E			
PRP Power	kVA	610			
LTP Power	kVA	665			
Winding		Three phases Series Star			
Terminals Number		12 nr.			
IP Protection		23			
Electronic regulator		AS440			
Precision	± 1.00 %				
The company reserves the right to modify the technical specifications, items					

The company reserves the right to modify the technical specifications, iter and design without notice. The images of the products are indicative for illustrative purposes only.



Trime UK Limited | B3 Spitfire Close, Huntingdon, Cambridgeshire PE29 6XY 01480 220500 | www.trimeuk.com | sales@trimeuk.com