## **Serkins**

URS	TKY41	N/ N/	
GENSET MODEL			
Model	MGTP 670 SS PI		
Mechanical version	Silenced version with galvanized steel sheet and powder-painted canopy, compact baseframe, with bunded tank and leak control		
Fuel Tank Capacity	lt.	950	
Rated technical data			
Prime Power (PRP)	kVA	670	
Prime Power (PRP)	KW	536	
Limited Power (LTP)	kVA	720	
Limited Power (LTP)	KW	576	
Rated Power Factor (cosφ)		0.8	
Windings		Three phases Series Star	
Rated three-phase concatenated Voltage	V	400	
Rated phase-neutral voltage	V	230	
Rated frequency	Hz	50	
Fuel type		Diesel	
Dimensions And Noise			
Length	mm	4500	
Width	mm	1840	
Height	mm	2540	
Weight	Kg	6250	
Sound pressure 7 m.	dBA	74	
Fuel consumption			
Fuel Cons. at 100% (LTP)	l/h	143	
Fuel Cons. at 100% (PRP)	l/h	132	
Fuel Cons. at 75% (PRP)	l/h	97	
Fuel Cons. at 50% (PRP)	l/h	66	
General Alternator Data			
Alternator brand		STAMFORD	
Alternator model		HCI5F	
PRP Power	kVA	670	
LTP Power	kVA	738	
Winding		Three phases Series Star	
Terminals Number		12 nr.	
IP Protection		23	
Electronic regulator		AS440	
Precision		± 1.00 %	
The same and a sharp sight to	ا بر بالم مع مرام بالأناب	all an additional itams 7	

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.



	General Engine Data				
	Engine brand		PERKINS		
	Engine model		2806A-E18TAG2		
	Cylinders		6		
	R.P.M.		1500		
	Cubic capacity		18130		
	Air intake		Turbo		
	Standard voltage	Vdc	24		
	Sae		-		
	BMEP	kPa	2576		
	Cooling		Water		
	Flywheel P.R.P. Power	kW	565		
	Flywheel Stand-by Power	kW	609		
	Electronic regulator		Standard		
	Precision class		G3		
	Oil quantity	lt.	62		
	EU Stage		Not available		
	Standard Foatures				

## Standard Features

Hard wires connection protected

Electrical panel ComAp AMF25 mounted on board with safety cover Circuit breaker

Internal exhaust gas silencer and insulated manifold Engine oil extraction pump and fuel decanter filter

12V Battery with battery switch

Bunded tank

Lifting hooks and side forklift pockets

## **Options** factory installed

220V Electric pre-heater

KIT socket TPS01: 1x32A, 1x16A 3Ph

1x16A 1Ph + 1x16A Schuko

1x63A, 1x32A, 1x16A 3Ph

KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko

125A breaker with adj. earth fault relay

Kit AMF and ATS panel

Predisposition for quick release fitting for external fuel tank

Oversize fuel tank

