## **INDUSTRIAL LINE**

## MGTP 80 SS PI

**Serkins**<sup>®</sup>

## **GENSET MODEL** Model

Mechanical version

Fuel Tank Capacity

Rated technical data Prime Power (PRP)

Prime Power (PRP)

Limited Power (LTP)

Limited Power (LTP)

Windings

Rated Power Factor (cos q)

## MGTP 80 SS PI Silenced version with galvanized steel sheet and powder-painted canopy, compact base frame, with bunded tank and leak control 160 lt. kVA 80 KW 64 kVA 88 KW 70,4 0.8 Three phases Series Star

		Series Star
Rated three-phase concatenated Voltage	V	400
Rated phase-neutral voltage	V	230
Rated frequency	Hz	50
Fuel type		Diesel
Dimensions And Noise		
Length	mm	2260
Width	mm	1040
Height	mm	1820
Weight	Kg	1500
Sound pressure 7 m.	dBA	65
Fuel consumption		
Fuel Cons. at 100% (LTP)	l/h	20,5
Fuel Cons. at 100% (PRP)	l/h	18,7
Fuel Cons. at 75% (PRP)	l/h	14
Fuel Cons. at 50% (PRP)	l/h	9,7
General Alternator Data		
Alternator brand		STAMFORD
Alternator model		UCI224G
PRP Power	kVA	85
LTP Power	kVA	90,8
Winding		Three phases Series Star
Terminals Number		12 nr.
IP Protection		23
Electronic regulator		SX460
Precision		± 1.50 %

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.

**Power Division** 



ta				
		PERKINS		
		1104A-44TG2		
		4		
		1500		
		4400		
		Turbo		
	Vdc	12		
		-		
	kPa	1335		
		Water		
/er	kW	71,9		
Power	kW	79,1		
or		On request		
		G2		
	lt.	8		
		Not available		
Hard wires connection protected				
Electrical panel DSE 4520 mounted on board with safety cover				
Circuit breaker				
Internal exhaust gas silencer and insulated manifold				
Engine oil extraction pump and fuel decanter filter				
12V Battery with battery switch				
Bunded tank				
Lifting hooks and side forklift pockets				
Options factory installed				
220V Electric pre-heater				
1x32A, 1x16A 3Ph 1x16A 1Ph + 1x16A Schuko				
1x63A, 1x32A, 1x16A 3Ph KIT socket TPS03: 1x16A 1Ph + 1x16A Schuko 125A breaker with adj. earth fault relay				
anel				
	ver Power power pr tion protecte E 4520 moun as silencer and on pump and attery switch side forklift po stalled heater 1x32A, 1x16/ 1x16A 1Ph + 1x63A, 1x32/ 1x16A 1Ph + 125A breaker	Vdc kPa ver kW Power kW Power kW or It. tion protected E 4520 mounted on board as silencer and insulated r on pump and fuel decanted attery switch side forklift pockets stalled transported istalled transported transported transported transported transported transported transported kW transported transported transported transported transported transported transported kW kW transported		

Predisposition for quick release fitting for external fuel tank Oversize fuel tank

Trime UK Limited | B3 Spitfire Close, Huntingdon, Cambridgeshire PE29 6XY 01480 220500 | www.trimeuk.com | sales@trimeuk.com