

MG 10000 CUBE

Welfare Cabin Ready 9.8kVA Diesel Generator

Optional extras:







9.8kVA (230V only) AC Aux Power

Mecc Alte alternator

Kubota diesel engine (Stage 5)

HVO (Hydrotreated Vegetable Oil) fuel approved

Emergency stop button

Central lifting eye

Engine protection shutdown system

Extremely compact

Welfare cabin ready

Benefits

Plenty of power for most welfare cabin applications

Heavy Duty and Proven reliability

World class performance, 1500rpm and watercooled

Suitable to run off either diesel or HVO

In the case of low fuel, low oil pressure, and battery charge failure

A must on any UK site

Flexible and safe lifting on site

Ideal when saving space is important

Easy fit, plug and play cabin installation









Performance

Alternator	Mecc Alte	(AVR)	Noise Level	LWA = 79 dBA@7	m = 54
Single Phase Power (1	10v)	N/A	Insulation Cla	SS	Н
Single Phase Power(230v) 9.8kVA / 7.8kW		Mechanical Protection - IP		23	
		- 7			

	Engine			
ĺ	Make	Kubota		
	Туре	D1105 (Stage 5)		
	Fuel Diesel / HVO (HVO = BS EN15940:2016 Only)			
	Number of Cylinder	s 3		
	Power (HP)	13.7		
	Engine Speed (RPM	<i>I</i>) 1500		
	Cooling	Water		

Fuel Consumption @ 75% Load (Ltr/Hr)			
Fuel Tank Capacity			
Average Runtime (Hrs)	@ 100% Load 20 hrs		
, ,	@ 75% Load 2	9 hrs	
@ 50% Lo		0 hrs	
	@ 25% Load 9	2 hrs	
CO ₂ Per Hour @ 75% Load 4		98kg	
('ontrol Panel	ea 3110 c/w two		

Dimensions & Weight (Machine only)

Length: 1100 mm	Width: 790mm	Height: 1000 mm	
Dry Weight (No Fuel): 425 kg		Wet Weight (Fuel Full): 475 kg	
Cooket Configuration	1ph 230v		
Socket Configuration		32a	
MG-5 10000 Cube (Welfare)		2	
Hard Wire Facility		1ph 230v	
MG-5 10000 Cube (Welfare)		1pii 250V	
ivid 3 10000 Jube (vveilale)		•	

