

MG 10000 CUBE

Welfare Cabin Ready 9.8kVA Diesel Generator




Optional extras:



Remote Start/Stop



Remote Start/Stop + timer control



Features

9.8kVA (230V only) AC Aux Power

Mecc Alte (AVR) alternator

Kubota diesel engine (Stage 5)

HVO (Hydrotreated Vegetable Oil) fuel approved

Emergency stop button

Central lifting eye

Engine protection shutdown system

Extremely compact

Welfare cabin ready

Benefits

Plenty of power for most welfare cabin applications

Heavy Duty and Proven reliability

World class performance, 1500rpm and watercooled

Suitable to run off either diesel or HVO

In the case of low fuel, low oil pressure, and battery charge failure

A must on any UK site

Flexible and safe lifting on site

Ideal when saving space is important

Easy fit, plug and play cabin installation

Specification

Performance

Alternator	Mecc Alte (AVR)	Noise Level	LWA = 79 dBA@7m = 54
Single Phase Power (110v)	N/A	Insulation Class	H
Single Phase Power(230v)	9.8kVA / 7.8kW	Mechanical Protection - IP	23

Engine

Make	Kubota	Fuel Consumption @ 75% Load (Ltr/Hr)	1.9
Type	D1105 (Stage 5)	Fuel Tank Capacity	55
Fuel Diesel / HVO (HVO = BS EN15940:2016 Only)		Average Runtime (Hrs)	@ 100% Load 20 hrs @ 75% Load 29 hrs @ 50% Load 40 hrs @ 25% Load 92 hrs
Number of Cylinders	3	CO ₂ Per Hour @ 75% Load	4.98kg
Power (HP)	13.7	Control Panel	Deepsea 3110 c/w two wire Auto Start/ Stop facility
Engine Speed (RPM)	1500		
Cooling	Water		



modular & portable building association



Dimensions & Weight (Machine only)

Length: 1100 mm	Width: 790mm	Height: 1000 mm
Dry Weight (No Fuel): 425 kg		Wet Weight (Fuel Full): 475 kg

Socket Configuration	1ph 230v 32a
MG-5 10000 Cube (Welfare)	1
Hard Wire Facility	1ph 230v
MG-5 10000 Cube (Welfare)	✓