

MG 9000 Compact

Welfare Cabin Ready 9kVA Diesel Generator

Optional extras:



Remote Start/Stop



Remote Start/Stop + timer control

Features

- 9kVA (230V only)
- Zanardi alternator
- Kubota diesel engine (Stage 5)
- HVO (Hydrotreated Vegetable Oil) fuel approved
- Engine protection shutdown system
- Central lifting eye and fork pockets
- Emergency stop button
- Extremely compact
- Welfare cabin ready

Benefits

- Plenty of power for most welfare cabin applications
- Heavy duty and proven reliability
- Power, reliability and robust strength
- Suitable to run off either diesel or HVO
- In the case of low fuel, low oil pressure, and battery charge failure
- Flexible and safe lifting on site.
- A must on any UK site
- Ideal when saving space is important
- Easy fit, plug and play cabin installation

Specification

Performance		
Alternator	Mecc Alte (AVR)	Noise Level LWA = 88 dBA@7m = 63
Single Phase Power (110v)	N/A	Insulation Class H
Single Phase Power(230v)	9kVA / 7.2kW	Mechanical Protection - IP 23
Engine		
Make	Kubota	Fuel Consumption @ 75% Load (Ltr/Hr) 1.9
Type	D1105 (Stage 5)	Fuel Tank Capacity 195 litres
Fuel	Diesel / HVO (HVO = BS EN15940:2016 Only)	Average Runtime (Hrs) @ 100% Load 70 hrs @ 75% Load 102 hrs @ 50% Load 162 hrs @ 25% Load 325 hrs
Number of Cylinders	3	CO ₂ Per Hour @ 75% Load 4.98kg
Power (HP)	13.7	Control Panel Deepsea 3110 c/w two wire Auto Start/ Stop facility
Engine Speed (RPM)	1500	
Cooling	Water	

Water Cooled
Extra Super
Silent

HVO
FUEL
APPROVED

WELFARE
CABIN
READY

1500
rpm

mpba

modular & portable
building association

STAGE 5
CERTIFIED

Dimensions & Weight (Machine only)

Length: 960 mm	Width: 680 mm	Height: 1785 mm
Dry Weight (No Fuel): 478 kg		Wet Weight (Fuel Full): 648 kg

Socket Configuration	1ph 230v		
	16a	32a	63a
PP102-10MS1	1	1	1
Hard Wire Facility	1ph 230v		
	✓		