

**MGMK 10000 CUBE** 

Welfare Cabin Ready 9.8kVA Longrun **Diesel Generator** 

Optional extras:





# **Features**

9.8kVA (230V only) AC Aux Power

Mecc Alte alternator

Kubota diesel engine (Stage 5)

HVO (Hydrotreated Vegetable Oil) fuel approved

Emergency stop button

Central lifting eye

Engine protection shutdown system

Extremely compact

Extra large base fuel tank

Welfare cabin ready

## **Benefits**

Plenty of power for most welfare cabin applications

Heavy Duty and Proven reliability

World class performance, 1500rpm and watercooled

Suitable to run off either diesel or HVO

In the case of low fuel, low oil pressure, and battery charge failure

A must on any UK site

Flexible and safe lifting on site

Ideal when saving space is important

To enable extremely long run time -157 hours @ 75% load

Easy fit, plug and play cabin installation



# **Specification**

### **Performance**

Alternator	Mecc Alte (AVR)		Noise Level	LWA = 79 dBA@	7m = 54
Single Phase Power (110v) N/A		Insulation Cla	ISS	Н	
Single Phase Power(230v) 9.8kVA / 7.8kW			Mechanical P	rotection - IP	23

Control Panel

Liigiile		
Make	Kubota	
Туре	D1105 (Stage 5)	
Fuel Diesel / HVO (HVO = BS EN15940:2016 Only)		
Number of Cylinder	s <b>3</b>	
Power (HP)	13.7	
Engine Speed (RPN	M) 1500	
Cooling	Water	

Fuel Consumption @ 75	5% Load (Ltr/Hr)	1.9
Fuel Tank Capacity		300
Average Runtime (Hrs)	@ 100% Load 107	hrs
0 ( )	@ 75% Load 157	hrs
	@ 50% Load 250	hrs
	@ 25% Load 500	hrs
CO <sub>2</sub> Per Hour @ 75% L	oad <b>4.9</b>	8kg
Cantral Danal Deeps	ea 3110 c/w two v	vire

Auto Start/ Stop facility

Dimensions & Weight (Machine only)

Length: 1115 mm	Width: 800 mm	Height: <b>1560</b> mm	
Dry Weight (No Fuel): 465 kg		Wet Weight (Fuel Full): 708 kg	
Cooket Configuration	1ph 230v		
Socket Configuration		32a	
PP38-10MS7	2		
Hard Wire Facility	1ph 230v		



PP38-10MS7