


MGMK 10000-300

Welfare Cabin Ready 9.8kVA Longrun Diesel Generator



Optional extras:



Remote Start/Stop



Remote Start/Stop + timer control

Features

- 9.8kVA (230V only) AC Aux Power
- Mecc Alte (AVR) alternator
- Kubota diesel engine (Stage 5)
- HVO (Hydrotreated Vegetable Oil) fuel approved
- Emergency stop button
- Central lifting eye
- Engine protection shutdown system
- Extremely compact
- Extra large base fuel tank
- Welfare cabin ready

Benefits

- Plenty of power for most welfare cabin applications
- Heavy Duty and Proven reliability
- World class performance, 1500rpm and watercooled
- Suitable to run off either diesel or HVO
- In the case of low fuel, low oil pressure, and battery charge failure
- A must on any UK site
- Flexible and safe lifting on site
- Ideal when saving space is important
- To enable extremely long run time – 157 hours @ 75% load
- Easy fit, plug and play cabin installation

Specification

Performance

Alternator	Mecc Alte (AVR)	Noise Level LWA = 79 dBA@7m = 54
Single Phase Power (110v)	N/A	Insulation Class H
Single Phase Power(230v)	9.8kVA / 7.8kW	Mechanical Protection - IP 23

Engine

Make	Kubota	Fuel Consumption @ 75% Load (Ltr/Hr)	1.9
Type	D1105 (Stage 5)	Fuel Tank Capacity	300
Fuel Diesel / HVO (HVO = BS EN15940:2016 Only)		Average Runtime (Hrs)	@ 100% Load 107 hrs @ 75% Load 157 hrs @ 50% Load 250 hrs @ 25% Load 500 hrs
Number of Cylinders	3	CO ₂ Per Hour @ 75% Load	4.98kg
Power (HP)	13.7	Control Panel	Deepsea 3110 c/w two wire Auto Start/ Stop facility
Engine Speed (RPM)	1500		
Cooling	Water		



modular & portable building association



Dimensions & Weight (Machine only)

Length: 1115 mm	Width: 800 mm	Height: 1560 mm
Dry Weight (No Fuel): 465 kg		Wet Weight (Fuel Full): 708 kg

Socket Configuration	1ph 230v 32a
PP38-10MS7	1
Hard Wire Facility	1ph 230v
PP38-10MS7	✓