

# MGMK 10000-300

## Welfare Cabin Ready 9.8kVA Longrun Diesel Generator

Optional extras:



Remote Start/Stop



Remote Start/Stop + timer control



### Features

9.8kVA (230V only) AC Aux Power

Mecc Alte alternator

Kubota diesel engine (Stage 5)

HVO (Hydrotreated Vegetable Oil fuel approved)

Emergency stop button

Central lifting eye

Engine protection shutdown system

Extremely compact

Extra large base fuel tank

Welfare cabin ready

### Benefits

Plenty of power for most welfare cabin applications

Heavy Duty and Proven reliability

World class performance, 1500rpm and watercooled

Suitable to run off either diesel or HVO

In the case of low fuel, low oil pressure, and battery charge failure

A must on any UK site

Flexible and safe lifting on site

Ideal when saving space is important

To enable extremely long run time – 157 hours @ 75% load

Easy fit, plug and play cabin installation

Water Cooled  
Extra Super  
Silent



1500  
rpm

### Specification

#### Performance

Alternator	Mecc Alte (AVR)	Noise Level	LWA = 79 dBA@7m = 54
Single Phase Power (110v)	N/A	Insulation Class	H
Single Phase Power(230v)	9.8kVA / 7.8kW	Mechanical Protection - IP	23

#### Engine

Make	Kubota	Fuel Consumption @ 75% Load (Ltr/Hr)	1.9
Type	D1105 (Stage 5)	Fuel Tank Capacity	300
Fuel Diesel / HVO (HVO = BS EN15940:2016 Only)		Average Runtime (Hrs)	@ 100% Load 107 hrs @ 75% Load 157 hrs @ 50% Load 250 hrs @ 25% Load 500 hrs
Number of Cylinders	3	CO <sub>2</sub> Per Hour @ 75% Load	4.98kg
Power (HP)	13.7	Control Panel	Deepsea 3110 c/w two wire Auto Start/ Stop facility
Engine Speed (RPM)	1500		
Cooling	Water		



modular & portable  
building association



#### Dimensions & Weight (Machine only)

Length: 1115 mm	Width: 800 mm	Height: 1560 mm
Dry Weight (No Fuel): 465 kg		Wet Weight (Fuel Full): 708 kg

#### Hard Wire Facility

1ph 230v

PP38-10MS7

