AIR COOLED ENGINE 3000 r.p.m.













3000 RPM

NOISE level

AIR cooled **GASOLINE**







	MGTP 11 AE	MGTP 12 AE 3F
Code	PP79-11MS0	PP80-12TS0
On board control panel equipped with:		
	- DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency Stop - Sounproof canopy - Exhaust gas silencer - 2x32A 1ph 230V EEC socket - 1x16A 1ph 230V EEC socket	- DSE ON/OFF switch - DSE 3110 module will display warnings, shutdowns & engine status information as high temperature, low oil pressure, low fuel level warning, Volts & Frequency, running hrs, battery voltage monitoring - Circuit breaker - Emergency Stop - Sounproof canopy - Exhaust gas silencer - 1x 16A 3Ph 400V EEC socket - 1x 32A 1Ph 230V EEC socket
Generator		
Туре	Linz E1C11M B	Linz E1S11M AS
Power	11 kVA 230V	12 kVA 400V
Frequency	50 Hz	50 Hz
Engine		
Engine type	HONDA GX630	HONDA GX630
N° cylinders	2	2
Power	20,8 HP	20,8 HP
Engine speed	3000 r.p.m.	3000 r.p.m.
Cooling	Air	Air
Fuel	Unleaded gasoline	Unleaded gasoline
Starting system	Electric	Electric
Dimensions & weight		
Fuel tank capacity	21 lt	21 lt
Running Time	4,4 hrs	4,4 hrs
Dry weight	204 Kg	204 Kg
Dimensions (L. x W. x H.)	970 x 600 x 750 mm	970 x 600 x 750 mm

OPTIONS



The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.

