PORTABLE LINE

designed and created for your needs

<u>MGTP</u> 10000SSKV





For a more sustainable & environmentally friendly future



PORTABLE LINE













WATER cooled

SINGLE phase

CIN	CI	E
SIII		-
ph	as	е



Code	PP14-10MS7
Distribution Panel	
1x 16A-115V CEE socket	
2x 32A-115V CEE socket	
1x 32A-230V CEE socket	
2x 16A-230V CEE socket	
Technical Data	
Single-phase power	10kVA - 230V
Single-phase power	10kVA - 115V
Power factor (cos φ)	0.8
Frequency	50 Hz
RPM	3000
Generator	
Model	LINZ E1C11M B
Insulation Class	Н
Mechanical Protection	IP23
Engine	
Туре	Kubota D722 *
EU Emission Stage	Stage 5
N. Cylinders	3
Displacement	719 cm ³
Starting system	Electric
Cooling	Water
Fuel	Diesel
Fuel Consumption	
Fuel Tank capacity	40 I
Fuel consumption 75% load PRP	2,8 l/h
Running time	14 h

Dimensions & Weight	
Dry weight	350 Kg
Dimensions (L. x W. x H.)	1250 x 970 x 1007 mm
Standard Features	
10kVA (230V / 110V) AC Aux Power	
Linz alternator	
Kubota electric start diesel engine (Stage 5)	
HVO (Hydrotreated Vegetable Oil) fuel approved	
Emergency stop button	
Central lifting eye and front & side fork pockets	
Fully bunded base (110%)	
Complete with trolley kit + folding handles	
On Board Control Panel Equipped With:	
DSE 3110 Controller and management unit includi	ing hour counter and volt meter
Emergency stop	
ELCB, Main protection	
Fuel level monitor	
Voltage selector: 115V/230V	
Noise Level	
Noise level	89 Lwa
Acoustic pressure level 7m	64 dbA

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.

*Alternative Kohler equivalent engine may be fitted

