

PORTABLE LINE  
STAGE V

designed and created  
for your needs

**MGTP**  
**15000SSK-MV**

**STAGE 5**  
**CERTIFIED**



For a more sustainable  
& environmentally  
friendly future

 **TRIME**<sup>®</sup>  
Power Division

## PORTABLE LINE STAGE V

# MGTP 15000SSK-MV



Code	RP280-15TS1
<b>Distribution Panel</b>	
3x 32A-110V EEC with CB	
1x 16A-110V EEC with CB	
1x 32A-400V EEC with CB	
2x 32A-230V EEC with CB	
1x 16A-230V EEC with CB	
400V Hardwire - 110V Hardwire	
<b>Technical Data</b>	
Three-phase power	15kVA - 400V
Single-phase power	3x 5 kVA - 230V
Single-phase power	12 kVA - 110V
Power factor (cos φ)	0.8
Frequency	50 Hz
RPM	3000
<b>Generator</b>	
Model	LINZ E1X13M E/2
Insulation Class	H
Mechanical Protection	IP23
<b>Engine</b>	
Type	Kubota D1105
EU Emission Stage	Stage V
N. Cylinders	3
Displacement	1123 cm <sup>3</sup>
Starting system	Electric
Cooling	Water
Fuel	Diesel

<b>Fuel Consumption</b>	
Fuel Tank capacity	45 l
Fuel consumption 75% load PRP	4.5 l/h
Running time	10 h
<b>Dimensions &amp; Weight</b>	
Dry weight	540 Kg
Dimensions (L. x W. x H.)	1500 x 700 x 950 mm
<b>Standard Features</b>	
Built in fuel tank	
12V Battery	
Forklift pockets	
Central lifting eye	
Kit trolley, handles and wheels	
Exhaust gas silencer	
Soundproof Canopy	
Manual oil extraction pump	
<b>On Board Control Panel Equipped With:</b>	
Control panel with DSE 3110 controller for auto start/stop	
DSE ON/OFF switch	
Fuel level monitor	
Main circuit breaker	
Earth leakage relay	
Remote start/stop connector	
Emergency stop	
<b>Noise Level</b>	
Noise level	93 Lwa

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.