

ULTRA SILENT LINE
STAGE 5

power
and innovation

STAGE 5
CERTIFIED

850 L
Fuel Tank
capacity

designed and created
for your needs

Designed to provide
an exceptional level
of performance
for every work on site
ensuring the right
balance between power
and ease of use

MGTP
200 USL-F



more sustainable
and environmentally
friendly future

 **TRIME**[®]
Power Division

MGTP 200 USL-F

GENSET MODEL



NOISE
level **54**
dB(A) at 7m

APPLICATIONS



Constructions



Mining operations



Events



Military applications

FEATURES

- ✔ Autostart logic panel DSE 7310 for Manual version
- ✔ 4-poles magnetothermic switch
- ✔ Adjustable ELCB circuit breaker
- ✔ Power terminal block protection microswitch
- ✔ Oil extraction pump
- ✔ Battery disconnect switch
- ✔ Mechanical fuel level gauge on tank
- ✔ 3-way valve for diesel circuit from ext. tank (quick couplings excluded)
- ✔ Side rubber bumper protection
- ✔ Water / Diesel separator filter
- ✔ AdBlue, urea tank included
- ✔ Central lifting hook
- ✔ Doors closing by compression
- ✔ Radiator in separate compartment
- ✔ Heavy duty air filter
- ✔ Liquid collection tank with alarm
- ✔ Tank inspection flange
- ✔ Reinforced chassis for Rental use
- ✔ Alternator with butadiene protection System 2 Leroy Somer or Total Plus MeccAlte

Fuel saving in 1000h operation* | 1300

* Compared to standard generators



Code	RP347-200TSO
------	---------------------

ULTRA SILENCED version, galvanized and powder-painted canopy, compact base frame, with bunded tank and leak control

Dimensions

L x W x H (mm)	4200 x 1130 x 2200
Weight (Kg)	4480

Technical Data

Prime Power (PRP)(kVA)	200
Prime Power (PRP)(kW)	160
Limited Power (LTP)(kVA)	220
Limited Power (LTP)(kW)	176
Rated Power Factor (cos ϕ)	0,8
Windings	Three phases Series Star
Rated three-phase concatenated voltage (V)	400
Rated phase-neutral voltage (V)	230
Rated frequency (Hz)	50
Fuel type	Diesel
Fuel tank capacity (l)	850
AD BLUE Tank Capacity	78

Fuel consumption

Fuel Cons. at 100% (L.T.P.)(l/h)	40,0
Fuel Cons. at 75% (P.R.P.)(l/h)	31,0
Fuel Cons. at 50% (P.R.P.)(l/h)	30,2
Fuel Cons. at 25% (P.R.P.)(l/h)	32,8

Alternator

Alternator brand	Leroy-Somer
Alternator model	LSA44.3L14
P.R.P. Power (kVA)	200
L.T.P. Power (kVA)	220
Winding	Three phases Series Star
Terminals Number	12
IP Protection	23
Voltage regulator	AVR $\pm 0,25\%$ D350 AREP
Short-circuit current	300 %: 10s

Engine

Engine brand	FPT
Engine model	NEF 67
Cylinders	6
R.P.M. (rpm)	1500
Cubic capacity (cc)	6728
Air intake	Turbo
Standard voltage (Vdc)	24
Sae	-
BMEP (kPa)	-
Cooling	Water
Flywheel P.R.P. Power (kW)	176,6
Flywheel Stand-by Power (kW)	194,3
Electronic regulator	Yes
Precision class	G2
Oil quantity (l)	17,2

Options: Rental Kit

5 x 16A 230V + 1 x 32A 400 V + 1 x 63A 400V with ELCB protection

Sound Pressure 7m (0% load)	dBA 54
------------------------------------	---------------

Standard reference conditions

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional



Trime UK Ltd | 1 Redwing Court, Falcon Road, Hinchingsbrooke Business Park, Huntingdon PE29 6FG
01480 220500 | www.trimeuk.com | sales@trimeuk.com

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.