

SOLAR  
HYBRID LINE

power  
and innovation

STAGE 5  
CERTIFIED

67 KVA  
combined power

8h run time

4 x 360W  
extendable solar panels

designed and created  
for your needs

Designed to provide  
an exceptional level  
of performance  
for every work on site  
ensuring the right  
balance between power  
and ease of use

MGTP  
30000/60 THS




more sustainable  
and environmentally  
friendly future

 **TRIME**<sup>®</sup>  
Power Division

# MGTP

## 30000/60 THS



**REDUCTION**  
emissions **CO<sub>2</sub>**

### APPLICATIONS



### FEATURES

- ✓ MRS 16 controller
- ✓ 5" Touch monitoring display controller
- ✓ Communication-centre device
- ✓ 48V/1000A BMS to protect the batteries
- ✓ 4G/GPS Antenna + Modem
- ✓ **Remote telemetry & management**
- ✓ Auto recharge of the batteries
- ✓ Automatic peak shaving mode
- ✓ Sides forklift pockets & Central lifting hook
- ✓ Lockable control panel
- ✓ Main circuit breaker & Earth leakage relay
- ✓ Emergency Stop button
- ✓ Bunded tank
- ✓ 3-way valve for external tank
- ✓ Battery switch

### Solar Panels

Power (W)	<b>360</b>
Q.ty	<b>4</b>
Type	<b>Monocrystalline</b>
Tilting	<b>Electric</b>
Solar charger	<b>MPPT 150/35</b>

**solar hybrid**  
technology



## SOLAR HYBRID LINE

Code	R RP313-30TS8S
<b>Dimensions</b>	
L x W x H (mm)	<b>3335x2210x2268</b>
Dray weight (Kg)	<b>3150</b>
<b>Technical Data</b>	
Continuous power (VA)	<b>30000</b>
Battery pack capacity (Wh)	<b>62259</b>
Capacity available DOD 80% (Wh)	<b>49807</b>
Voltage (V)	<b>230/400</b>
Frequency (Hz)	<b>50</b>
<b>Inverter</b>	
Nominal power (VA)	<b>10000</b>
Q.ty	<b>3</b>
System voltage (V)	<b>48</b>
Max charging current (A)	<b>140</b>
<b>Batteries</b>	
Type	<b>LiFePO<sub>4</sub></b>
Q.ty	<b>8</b>
Nominal Voltage (V)	<b>25,6</b>
Nominal Capacity (Ah)	<b>304</b>
Cycle Life DOD 80%	<b>&gt;4000</b>
<b>Engine</b>	
Brand	<b>Kohler</b>
Model	<b>KDI2504TCR</b>
Speed	<b>1500</b>
Cooling system	<b>Water</b>
Emission	<b>Stage V</b>
Fuel Tank (l)	<b>700</b>
<b>Alternator</b>	
Brand	<b>Linz</b>
Model	<b>PRO 22S C/4</b>
Rated output (kVA)	<b>85</b>
Frequency (Hz)	<b>50</b>
Power factor (cos φ)	<b>0,8</b>
<b>Distribution panel</b>	
Inlet Plug	<b>1x 63A-400V</b>
	<b>1x 63A-400V</b>
Outlet Sockets	<b>1x 32A-400V</b>
	<b>1x 16A-230V</b>
<b>Performances</b>	
Running time on batteries (h) 25% load	<b>8,0</b>
Running time on batteries (h) 50% load	<b>4,0</b>
Running time on batteries (h) 75% load	<b>2,5</b>
Recharge time from engine (h)	<b>5</b>
<b>Available options</b>	
RSV 32A plug + MPPT solar charger for external solar panels	
Mat heating system for batteries to work in cold ambients	
OptionGEN PRO controller c/w remote check & management and CO <sub>2</sub> -Fuel savings calculator	



**easy handling & transportability**



**Trime UK Ltd** | 1 Redwing Court, Falcon Road, Hinchingsbrooke Business Park, Huntingdon PE29 6FG  
01480 220500 | [www.trimeuk.com](http://www.trimeuk.com) | [sales@trimeuk.com](mailto:sales@trimeuk.com)

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.