

PORTABLE LINE
DIESEL

power
and innovation

STAGE 5
CERTIFIED

designed and created
for your needs

Designed to provide
an exceptional level
of performance
for every work on site
ensuring the right
balance between power
and ease of use

MGTP
6000SSY



more sustainable
and environmentally
friendly future

 **TRIME**[®]
Power Division

MGTP 6000SSY

PORTABLE LINE
DIESEL



Kubota



AIR COOLED
ENGINE
3000 r.p.m.



Code	PP15-6MSS1-2
Dimensions	
L x W x H (mm)	1010 x 780 x 1000
Dray Weight (Kg)	206
Technical Data	
Fuel Tank Capacity (l)	25
Fuel consumption 75% load PRP (l)	1,4
Running Time (h)	18
Single-phase power	6kVA - 230V
Single-phase power	6kVA - 115V
Power factor (cos φ)	0.8
Frequency	50 Hz
RPM	3000
Noise level	90 Lwa
Acoustic pressure level 7m	65 dbA

Distribution panel	
2x 16A-115V CEE socket	
1x 32A-115V CEE socket	
1x 32A-230V CEE socket	
1x 16A-230V CEE socket	

Generator	
Type	LINZ E1C10M H
Insulation Class	H
Mechanical protection	IP23

Engine	
Type	Yanmar L100 AE
Cylinders	1
EU Emission Stage	Stage 5
Displacement (cm ³)	435
Cooling	Air
Fuel	Diesel
Starting system	Electric

On board control panel equipped with:	
- DSE 3110 Controller and management unit including hour counter and volt meter	
- Emergency stop	
- ELCB, Main protection	
- Voltage selector: 115V/230V	

APPLICATIONS



FEATURES

- ✓ 6kVA (230V / 110V) AC Aux Power
- ✓ Linz alternator
- ✓ Yanmar electric start diesel engine (Stage 5)
- ✓ HVO (Hydrotreated Vegetable Oil) fuel approved
- ✓ Emergency stop button
- ✓ Central lifting eye and front & side fork pockets
- ✓ Complete with trolley kit + folding handles



Trime UK Ltd | 1 Redwing Court, Falcon Road, Hinchingsbrooke Business Park, Huntingdon PE29 6FG
01480 220500 | www.trimeuk.com | sales@trimeuk.com

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.