HYBRID LINE

designed and created for your needs

power and innovation



15 KVA combined power

6h run time



Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

MGTP 8000/12 TH



more sustainable and environmentally friendly future



MGTP 8000/12 TH







APPLICATIONS









FEATURES

- DSE 3110 controller
- Communication-centre device
- 48V/400A BMS to protect the batteries
- Remote telemetry & management
- Auto recharge of the batteries
- Automatic peak shaving mode
- Sides forklift pockets & Central lifting hook
- Lockable control panel
- Main circuit breaker & Earth leakage relay
- Emergency Stop button
- Bunded tank
- 3-way valve for external tank
- Battery switch



HYBRID LINE

Code	RP47-8MS12
Dimensions	
xWxH(mm)	1700x1066x1450
Veight (Kg)	920
echnical Data	
Continuous power (VA)	8000
lattery pack capacity (Wh)	11776
Capacity available DOD 80% (Wh)	9421
oltage (V)	230
requency (Hz)	50
nverter	
lominal power (VA)	8000
).ty	1
System voltage (V)	48
lax charging current (A)	110
atteries	
ype	LiFeP04
l.ty	2
Iominal Voltage (V)	25,6
lominal Capacity (Ah)	230
ycle Life DOD 80%	>4000
ngine	
rand	Kubota
odel	D1105
peed	1500
ooling system	Water
mission	Stage V
uel Tank (I)	200
lternator	
rand	Linz
odel	PRO 18S A/4
ated output (kVA)	20
requency (Hz)	50
ower factor (cos φ)	0,8
istribution panel	
nlet Plug	1x 32A-230V
Outlet Sockets	1x 32A-230V
	1x 16A-230V
Performances	
dunning time on batteries (h) 25% load	6,0
Running time on batteries (h) 50% load	3,0
Running time on batteries (h) 75% load	2,0
	3,5
Recharge time from engine (h)	





Trime UK Ltd | 1 Redwing Court, Falcon Road, Hinchingbrooke Business Park, Huntingdon PE29 6FG 01480 220500 | www.trimeuk.com | sales@trimeuk.com