

LED TECHNOLOGY

**28.000 sqm**  
Illuminated Area

**ENGINE POWERED Line**



Operation: **ENGINE POWERED**  
fuel tank capacity 160 litres  
Kubota D1105




**X-DOUBLE**  
12X320W LED - 8,5M

## X-DOUBLE 12X320W LED - 8M



### FEATURES

- Multi-directionally adjustable and tiltable floodlights
- **No. 2 vertical mast, each: 7 sections hydraulic vertical tower 8 m, 340° rotatable**
- Galvanized metalworks
- 80 µm powder coating
- **Double lifting eyes and forklift pockets for effective handling**
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Digital control panel and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- **Fully bunded tank, 110%**
- Certified wind stability up to 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization



Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total Weight (kg)				
		2410x1425x2520 (LxWxH)		2410x2683x8000 (LxWxH)		1744			
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)				
	LED	320W	12	65	28.000				
Mast	Lifting method	Max Height		Max Wind Speed	Rotation				
	Hydraulic	8 m		110 km/h	340°				
Generator	Model	Frequency (Hz)	Rated Output	Power available to auxiliary socket	Rated voltage				
	Synchronous	50	8 kVA	3 kVA	230V				
Engine	Model	Fuel	r.p.m.	Tank capacity (l)	Consumption (l/h)	Running time	Noise level dB(A) at 7m	Displacement cm <sup>3</sup>	Cooling system
	Kubota D1105*	Diesel	1500	160	1,6	100 h	65	1123	Liquid

\* May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used