




LED TECHNOLOGY

**9300 sqm**  
Illuminated area



**PLUG-IN** Line



Operation: **POWER**  
Inlet plug 16A - 230V  
Outlet socket 16A - 230V

**X-MAST**  
4X320W LED - 8,5M  
**T-ZERO** PRO

## X-MAST

4x320W LED - 8,5M

### T-ZERO<sup>PRO</sup>



### FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 8,5 meters vertical tower, 340° rotatable
- **Manual lifting system by winch complete with auto-braking system**
- Galvanized metalworks
- 80 µm powder coating
- **Very compact dimensions, up to 22 units per truck**
- Sites forklift pockets
- Top and sides forklift pockets for effective handling
- Guided main coiled cable to avoid damage during tower operation
- Circuit breaker for electrical protection against overload
- Certified wind stability up to 110 km/h
- 4 extendable & height adjustable stabilizers
- Inlet plug and outlet socket to connect in series more units

**ZERO emissions**

**ZERO fuel costs**

**ZERO noise**

**MINIMAL service**

**EASY handling & transportability**

**LINKABLE TOWERS**

**9300 sqm illuminated area**

**Complete SILENCE**  
on work time  
**8 HOURS A DAY**  
**7 DAYS A WEEK**

**22 units per truck**   
**VERY COMPACT dimensions**

Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)	
	1100x1100x2650 (LxWxH)		2360x2360x8500 (LxWxH)		445	
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)	Options
	Led	320W	4	65	9300	Light sensor
Mast	Lifting method	Max Height	Max Wind Speed		Rotation	
	Manual	8,5 m	110 km/h		340°	
Input&output	Inlet plug		Outlet socket			
	16A - 230V		16A - 230V			