designed and creater for your needs

150-160m water onebulizer

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

TKS-160

SKID

TRIME



more sustainable and environmentally friendly future



T-ZEROPRO

150-160**m**

nebulizer

0-35°

340°

water 🌢





R.O.T. SYSTEM

150-160 m

- Remote control, 50m range programmable function"cicle" to start electricmotor-water pump – oscillation with only one button • Automatic oscillation 0 – 340° manual area setting
- Electric Tilting System

Technical data	
Electric engine power (kW)	150
Water consumption (l/m)	160 - 180
Coverage (without wind) (m)	150 - 160
Max. water throw height (m)	50
Water connection	UNI 45 or STORZ or CAMLOCK
Min. inlet Water pressure (bar)	1,0
Water inlet filter (mesh)	60
Y Filter (µm)	500
Electric tilting system	0 - 35°
Automatic oscillation	0 - 340°
Dimensions (mm)	2800x2600x2450
Weight (kg)	3370

emissions

Electric engine

APPLICATIONS



FEATURES

- SMART START SYSTEM
- Emergency stop button
- Separate electric cabinet
- Water pump
- Water pressure Gauge
- Water Safety pressure switch
- Lifting eye
- Stainless steel crowns with 72 nozzles
- Automatic Water drain system
- Mounted on base with forklift pockets

SAFETY

- Reduce dust for healty and safe environment
- Safety automatic clutch compliant with HSE norm
- Remote control with full operation
 - start/stop
 - tilt up/down
 - turn left/right/auto

OPTIONS

- 60 Hz
- External pump for chemicals additives



