designed and creater for your needs

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

TKS-50

40-50M water onebulizer



more sustainable and environmentally friendly future







APPLICATIONS

emissions



ZERO

FEATURES

- Integrated control panel
- SMART START SYSTEM
- Emergency stop button
- Phase inverter
- Water pump
- Water pressure Gauge
- Water Safety pressure switch
- Manual water drain system
- Central lifting eye
- Forklift pockets
- Stainless steel crown with 24 nozzles
- 3 height adjustable stabilizers
- Equipped with big size wheels for off-road site

Electric engine

SAFETY

- Reduce dust for healty and safe environment
- Safety automatic clutch compliant with HSE norm
- Remote control with full operation
 - start/stop
 - tilt up/down
 - turn left/right/auto

OPTIONS

- 60 Hz
- External pump for chemicals additives
- Front jockey wheel

- to start electricmotor-water pump oscillation with only one button Automatic oscillation 0 340° manual area setting
- Electric Tilting System

Technical data	
Electric engine power (kW)	15
Inlet plug	400V3P+N+T 50Hz 32A
Fan diameter (mm)	900
Water consumption (I/m)	37 - 43
Coverage (without wind)(m)	40 - 50
Water connection	UNI 45 or STORZ or CAMLOCK
Max. water throw height (m)	15
Min. inlet Water pressure (bar)	1.0
Generator required (kVA)	20
Water inlet filter (Mesh)	60
Y Filter (μm)	500
Electric tilting system	0 - 35°
Automatic oscillation	0 - 340°
Dimensions min (mm)	2077x1836x2230
Dimensions max (mm)	2877x1836x2230
Weight (kg)	840



