designed and created for your needs

50-60**m** water 🌢 nebulizer

Designed to provide an exceptional level of performance for every work on site ensuring the right balance between power and ease of use

ZEROPRO TRIME **TKS-60**

TKS-60

Generator required

more sustainable and environmentally friendly future







emissions **APPLICATIONS**



ZERO

FEATURES

- Integrated control panel
- SMART START SYSTEM
- Emergency stop button
- Phase inverter
- Water pump
- Water pressure Gauge
- Water Safety pressure switch
- Manual water drain system
- Central lifting eye
- Forklift pockets
- Stainless steel crown with 24 nozzles
- 3 height adjustable stabilizers
- Equipped with big size wheels for off-road site

00º/o

Electric engine

SAFETY

- Reduce dust for healty and safe environment
- Safety automatic clutch compliant with HSE norm
- Remote control with full operation
 - start/stop
 - tilt up/down
 - turn left/right/auto

OPTIONS

- 60 Hz
- External pump for chemicals additives
- Front jockey wheel

٠	Ο.	•••	•	٠	•	٠	 •	

- Remote control, 50m range programmable function"cicle" to start electricmotor-water pump – oscillation with only one button
 • Automatic oscillation 0 – 340° manual area setting
- Electric Tilting System

Technical data					
Electric engine power (kW)	22				
Inlet plug	400V3P+N+T 50Hz 32A				
Fan diameter (mm)	900				
Water consumption (I/m)	37 - 43				
Coverage (without wind) (m)	50 - 60				
Water connection	UNI 45 or STORZ or CAMLOCK				
Max. water throw height (m)	20				
Min. inlet Water pressure (bar)	1.0				
Generator required (kVA)	30				
Water inlet filter (Mesh)	60				
Y Filter (μm)	500				
Electric tilting system	0 - 35°				
Automatic oscillation	0 - 340°				
Dimensions min (mm)	2077x1836x2230				
Dimensions max (mm)	2877x1836x2230				
Weight (kg)	920				



