

## **RENTAL LINE – STAGE 5**

## MGTP 100 SS FR

## **DIESEL ENGINE DRIVEN GENERATING SET** 1500 RPM













NOISE level

WATER cooled

DIESEL

MGTP 100 SS FR	
Code	TBD
DISTRIBUITION PANEL	
1x125A + 1 x 63A 400V	
3 x 32A 230 V	
230V Hardwire	
400V Hardwire	

TECHNICAL DATA	
PRP Prime Power	100 kVA
LTP Limited Time Power	110 kVA
Prime Power (cos $\phi$ = 0,8)	80 kW
Limited Time Power ( $\cos \varphi = 0.8$ )	88 kW
Three-phase voltage	400 V
Single-phase voltage	230 V
Power factor (cos φ)	0,8
Frequency	50 Hz
RPM	1500

GENERATOR	
LINZ / MECC ALTE / STAMFORD	
Insulation Class	Н
Mechanical protection	IP23

ENGINE	
Туре	FTP IVECO F36 ETVPO3.A94
EU Emission Stage	Stage 5
N. Cylinders	4
Displacement	3400 cm <sup>3</sup>
Speed regulation	Electrical
Cooling	Water
Fuel	Diesel

FUEL CONSUMPTION	
Fuel tank capacity	250 l
Fuel consumption 75% load PRP	14 l/h
Running time	17 h

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.



FEATURES
Built in fuel tank
Bunded tank
12V Battery
Battery switch
Forklift pocket
Central lifting eye
Exhaust gas silencer
Soundproof canopy
3 ways valve for external fuel tank connection

X ( ) ( ) ( ) ( )
ON BOARD CONTROL PANEL EQUIPPED WITH:
DSE 7310 controller
ON/OFF switch
Safety cover for DSE controller and ON/OFF switch
Main circuit breaker
Earth leakage relay
Remote start/stop connector
Emergency stop

NOISE LEVEL		
Noise level	93 Lwa	
Acoustic pressure level 7m	68 dbA	

ROUGHLY DIMENSIONS & WEIGHT	
Dry weight	1688 Kg
Dimensions (L. x W. x H.)	2600x1180x1620 mm



Trime UK Ltd | 1 Redwing Court, Falcon Road, Hinchingbrooke Business Park, Huntingdon PE29 6FG 01480 220500 | www.trimeuk.com | sales@trimeuk.com