

PORTABLE LINE
STAGE V

designed and created
for your needs

MGTP
15000SSK-MV

STAGE 5
CERTIFIED



For a more sustainable
& environmentally
friendly future

 **TRIME**[®]
Power Division

PORTABLE LINE STAGE V

MGTP 15000SSK-MV



Code	RP280-15TS1
Distribution Panel	
3x 32A-110V EEC with CB	
1x 16A-110V EEC with CB	
1x 32A-400V EEC with CB	
2x 32A-230V EEC with CB	
1x 16A-230V EEC with CB	
400V Hardwire - 110V Hardwire	
Technical Data	
Three-phase power	15kVA - 400V
Single-phase power	3x 5 kVA - 230V
Single-phase power	12 kVA - 110V
Power factor (cos φ)	0.8
Frequency	50 Hz
RPM	3000
Generator	
Model	LINZ E1X13M E/2
Insulation Class	H
Mechanical Protection	IP23
Engine	
Type	Kubota D1105
EU Emission Stage	Stage V
N. Cylinders	3
Displacement	1123 cm ³
Starting system	Electric
Cooling	Water
Fuel	Diesel

Fuel Consumption	
Fuel Tank capacity	45 l
Fuel consumption 75% load PRP	4.5 l/h
Running time	10 h
Dimensions & Weight	
Dry weight	540 Kg
Dimensions (L. x W. x H.)	1500 x 700 x 950 mm
Standard Features	
Built in fuel tank	
12V Battery	
Forklift pockets	
Central lifting eye	
Kit trolley, handles and wheels	
Exhaust gas silencer	
Soundproof Canopy	
Manual oil extraction pump	
On Board Control Panel Equipped With:	
Control panel with DSE 3110 controller for auto start/stop	
DSE ON/OFF switch	
Fuel level monitor	
Main circuit breaker	
Earth leakage relay	
Remote start/stop connector	
Emergency stop	
Noise Level	
Noise level	93 Lwa

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.