PORTABLE LINE
STAGE V

designed and created
for your needs

MGTP
15000SSK-MV

STAGE 5
CERTIFIED

For a more sustainable
& environmentally
friendly future

TRIME®
Power Division

PORTABLE LINE
STAGE V

MGTP
15000SSK-MV

Kubota | 3000 RPM | WATER cooled | DIESEL

Code	**RP280-15TS1**
Distribution Panel	
3x 32A-110V EEC with CB	
1x 16A-110V EEC with CB	
1x 32A-400V EEC with CB	
2x 32A-230V EEC with CB	
1x 16A-230V EEC with CB	
400V Hardwire - 110V Hardwire	
Technical Data	
Three-phase power	**15kVA - 400V**
Single-phase power	**3x 5 kVA - 230V**
Single-phase power	**12 kVA - 110V**
Power factor (cos ϕ)	**0.8**
Frequency	**50 Hz**
RPM	**3000**
Generator	
Model	**LINZ E1X13M E/2**
Insulation Class	**H**
Mechanical Protection	**IP23**
Engine	
Type	**Kubota D1105**
EU Emission Stage	**Stage V**
N. Cylinders	**3**
Displacement	**1123 cm³**
Starting system	**Electric**
Cooling	**Water**
Fuel	**Diesel**

Fuel Consumption	
Fuel Tank capacity	**45 l**
Fuel consumption 75% load PRP	**4.5 l/h**
Running time	**10 h**
Dimensions & Weight	
Dry weight	**450 Kg**
Dimensions (L. x W. x H.)	**1500 x 790 x 935 mm**
Standard Features	
Built in fuel tank	
12V Battery	
Forklift pockets	
Central lifting eye	
Exhaust gas silencer	
Soundproof Canopy	
Manual oil extraction pump	
On Board Control Panel Equipped With:	
Control panel with DSE 3110 controller for auto start/stop	
DSE ON/OFF switch	
Fuel level monitor	
Main circuit breaker	
Earth leakage relay	
Remote start/stop connector	
Emergency stop	
Noise Level	
Noise level	**93 Lwa**

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.

TRIME®

Trime UK Ltd | 1 Redwing Court, Falcon Road, Hinchingbrooke Business Park, Huntingdon PE29 6FG
01480 220500 | www.trimeuk.com | sales@trimeuk.com