



TRIME®
Power Division




MGTP 20 SS YR

RENTAL LINE – STAGE 5

RENTAL LINE – STAGE 5

MGTP 20 SS YR

DIESEL ENGINE DRIVEN GENERATING SET 1500 RPM



MGTP 30 SS YR

Code TBD

DISTRIBUTION PANEL

2 x 32A 400 V

3 x 32A 230 V + 2 16A 230V

400V Hardwire

230V Hardwire

TECHNICAL DATA

PRP Prime Power	32 kVA
LTP Limited Time Power	35 kVA
Prime Power (cos φ = 0,8)	25,6 kW
Limited Time Power (cos φ = 0,8)	28 kW
Three-phase voltage	400 V
Single-phase voltage	230 V
Power factor (cos φ)	0,8
Frequency	50 Hz
RPM	1500

GENERATOR

LINZ / MECC ALTE / STAMFORD

Insulation Class	H
Mechanical protection	IP23

ENGINE

Type	Yanmar 4TNV88
EU Emission Stage	Stage 5
N. Cylinders	3
Displacement	2216 cm ³
Speed regulation	Electrical
Cooling	Water
Fuel	Diesel

FUEL CONSUMPTION

Fuel tank capacity	130 l
Fuel consumption 75% load PRP	6,7 l/h
Running time	19 h

FEATURES

Built in fuel tank
Bunded tank
12V Battery
Battery switch
Forklift pocket
Central lifting eye
Exhaust gas silencer
Soundproof canopy
3 ways valve for external fuel tank connection

ON BOARD CONTROL PANEL EQUIPPED WITH:

DSE 7310 controller
ON/OFF switch
Safety cover for DSE controller and ON/OFF switch
Main circuit breaker
Earth leakage relay
Remote start/stop connector
Emergency stop

NOISE LEVEL

Noise level	90 Lwa
Acoustic pressure level 7m	65 dbA

ROUGHLY DIMENSIONS & WEIGHT

Dry weight	1135 Kg
Dimensions (L. x W. x H.)	2200 x 1100 x 1618 mm



The company reserves the right to modify the technical specifications, items and design without notice.
The images of the products are indicative for illustrative purposes only.



TRIME

Trime UK Ltd | 1 Redwing Court, Falcon Road, Hinchingsbrooke Business Park, Huntingdon PE29 6FG
01480 220500 | www.trimeuk.com | sales@trimeuk.com

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.