

RENTAL LINE – STAGE 5

MGTP 30 SS YR

DIESEL ENGINE DRIVEN GENERATING SET 1500 RPM







1





≪YANMAR

1500 DDM

ISE WATER cooled

DIESEL



MGTP 30 SS YR

Code TBD

DISTRIBUITION PANEL

1 x 63A + 1 x 32A 400 V

3 x 32A 230 V

400V Hardwire

230V Hardwire

	CAL	

PRP Prime Power	32 kVA
LTP Limited Time Power	35 kVA
Prime Power ($\cos \varphi = 0.8$)	25,6 kW
Limited Time Power ($\cos \phi = 0.8$)	28 kW
Three-phase voltage	400 V
Single-phase voltage	230 V
Power factor ($\cos \phi$)	0,8
Frequency	50 Hz
RPM	1500

GENERATOR

LINZ / MECC ALTE / STAMFORD

Insulation Class H
Mechanical protection IP23

ENGINE

Туре	Yanmar 4TNV98
EU Emission Stage	Stage 5
N. Cylinders	3
Displacement	1861 cm ³
Speed regulation	Electrical
Cooling	Water
Fuel	Diesel

FUEL CONSUMPTION

Fuel tank capacity	130
Fuel consumption 75% load PRP	6,7 l/h
Running time	19 h

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.

FEATURES

Built in fuel tank

Bunded tank

12V Battery

Battery switch

Forklift pocket

Central lifting eye Exhaust gas silencer

Soundproof canopy

3 ways valve for external fuel tank connection

ON BOARD CONTROL PANEL EQUIPPED WITH:

DSE 7310 controller

ON/OFF switch

Safety cover for DSE controller and ON/OFF switch

Main circuit breaker

Earth leakage relay

Remote start/stop connector

Emergency stop

NOISE LEVEL

Noise level	90 Lwa
Acoustic pressure level 7m	65 dbA

ROUGHLY DIMENSIONS & WEIGHT

Dry weight	1135 Kg
Dimensions (L. x W. x H.)	2200 x 1100 x 1618 mm



Trime UK Ltd | 1 Redwing Court, Falcon Road, Hinchingbrooke Business Park, Huntingdon PE29 6FG 01480 220500 | www.trimeuk.com | sales@trimeuk.com