


SOLAR HYBRID LINE

MGTP 15000/24 THS

T-ZERO PRO

POWER & INNOVATION



YANMAR



1500 RPM



DIESEL



WATER cooled



SINGLE phase



THREE phase



SOLAR HYBRID technology



LITHIUM battery

STAGE 5
CERTIFIED

MGTP 15000/24 THS

Code **RP117-15TS8S**

Technical data

Continuous power (VA)	15000
Battery pack capacity (Wh)	23552
Capacity available DOD 80% (Wh)	18842
Voltage (V)	230/400
Frequency (Hz)	50

Inverter

Nominal power (VA)	5000
QTY	3
System voltage (V)	48
Max charging current (A)	70

Batteries

Type	LiFePO4
QTY	4
Nominal Voltage (V)	25,6
Nominal Capacity (Ah)	230
Cycle Life DOD 80%	> 4000

Solar Panels

Power	40
QTY	4
Type	Monocrystalline
Tilting	Electric
Solar charger	MPPT 150/35

Engine

Brand	Yanmar
Model	4TNV88
Speed	1500
Cooling system	Water
Emission	Stage V
Fuel Tank (l)	320

Alternator

Brand	Linz
Model	PRO 18M E/4
Rated output (kVA)	42
Frequency (Hz)	50
Power factor (cos φ)	0,8

Distribution Panel

Inlet Plug	1x 32A-400V
	1x 32A-400V
Outlet Sockets	1x 16A-400V
	1x 16A-230V

Performances

Running time on batteries (h) 25% load	5,0
Running time on batteries (h) 50% load	2,5
Running time on batteries (h) 75% load	1,5
Recharge time from engine (h)	3,5

Standard Features

DSE 3110 controller	Sides forklift pockets & Central lifting hook
5" Touch monitoring display controller	Lockable control panel
Communication-centre device	Main circuit breaker & Earth leakage relay
48V/400A BMS to protect the batteries	Emergency Stop button
4G/GPS Antenna + Modem	Bunded tank
Remote telemetry & management	3-way valve for external tank
Auto recharge of the batteries	Battery switch
Automatic peak shaving mode	

Available options

- MC4 connectors + MPPT solar charger for external solar panels
- Mat heating system for batteries to work in cold temperatures

Dimension

Length (mm)	2180
Width (mm)	1222
Height (mm)	1585
Dry weight (Kg)	1470

The company reserves the right to modify the technical specifications, items and design without notice. The images of the products are indicative for illustrative purposes only.