DIESEL ENGINE DRIVEN GENERATING SET 1500 r.p.m.



≫YANMAR

















MGTP 20 SSY MV		
Code		RP248-20TS7
TECHNICAL DATA		
PRP Prime Power	kVA	20
LTP Limited Time Power	kVA	21
Prime Power (cos ϕ = 0,8)	kW	16
Limited Time P. ($\cos \phi = 0.8$)	kW	16,8
Three-phase Voltage	٧	400
Single-phase Voltage	V	230 + 115
Power factor (cos φ)		0.8
Frequency	Hz	50
RPM		1500
GENERATOR		
LINZ / MECC ALTE / STAMFORD		
Insulation Class		Н
Mechanical protection		IP23
ENGINE		
Туре	YANMAR	R 4TNV88
EU Emission Stage		Stage V
N° cylinders		4
Displacement	cm³	2216
Speed regulation		Mechanical
Cooling		Water
Fuel		Diesel
Oil sump capacity	lt.	10,6
FUEL CONSUMPTION		
Fuel Tank capacity	lt.	203
Fuel consumption 75% load PRP	l/h	4,0
Running time	h	32
NOISE LEVEL		
Noise level	Lwa	88
Acoustic pressure level 7m	dBA	63
DIMENSIONS & WEIGHT		
Dry weight	Kg	907.5
	_	

The company reserves the right to modify the technical specifications, items and design without notice.
The images of the products are indicative for illustrative purposes only.

mm

1850 x 90 x 1510



GERTER	
• •	O TRIME Power Dream
The state of the s	

DISTRIBUTION PANEL:

1x 32A 400V EEC with MCB

2x 32A 230V EEC with MCB + ELCB

2x 16A 230V EEC with MCB + ELCB

3x 32A 115V EEC with MCB

1x 16A 115V EEC with MCB

Hardwire

ELR

STANDARD FEATURES:

Built in fuel tank

Bunded tank

12V Battery

Battery switch

Forklift pocket

Central lifting eye

Exhaust gas silencer

Soundproof canopy

2 way valve for external fuel tank connection

ON BOARD CONTROL PANEL EQUIPPED WITH:

DSE 7310

ON/OFF switch

Safety cover for DSE 3110 + ON/OFF switch

Main circuit breaker

Earth leakage relay

Remote start/stop connector

Emergency stop

OPTIONS



Site tow trailer



Road tow trailer



Dimensions (L. x W. x H.)