


**DIESEL ENGINE SPEED**  
3000 r.p.m.



Chopper System

### GW 15/400 SSK

Code	<b>WE20-15TS0</b>
<b>General features</b>	
Noise level	LWA = 88 dBa@7m = 63
Battery	45 Ah - 12 V
Fuel tank capacity	60 lt
Dimensions (L. x W. x H.)	1410 x 700 x 835 mm
Dry weight	500 kg

### Welding output

Rated output at 60% duty cycle	400 A - 30 V
Range of continuous control	10 ÷ 400 A
Striking voltage	70 V
Electrodes diameter	8 mm

### Auxiliary power

Type	ZANARDI EPW3
Single phase power	10 kVA 230 V
Three phase power	15 kVA 400 V
Frequency	50 Hz
Cosφ	0,8
Insulation class	H
Mechanical protection	IP 23

The company reserves the right to modify the technical specifications, items and design without notice.  
The images of the products are indicative for illustrative purposes only.

### Engine

Engine type	KUBOTA D1105-E
N° cylinders	3
Power	26 HP
Engine speed	3000 r.p.m.
Cooling	Water
Fuel	Diesel
Starting system	Electric

### Description

- Arc force regulation
- Overtemperature signal lamp
- Arc force switch
- Welding ON signal lamp
- Welding current regulation
- Fuel level monitor
- Battery charger failure signal lamp
- Low oil pressure signal lamp
- High coolant temperature signal lamp
- Fuel reserve signal lamp
- Glow plug signal lamp
- Hour counter
- Starting key
- Emergency stop
- Idle switch
- Earth leakage circuit breaker
- 415V socket protection
- 32A 230V socket protection
- 32A 110V socket protection
- Welding socket: Positive pole (+)
- Welding socket: Negative pole (-)
- Remote control connector
- 32A 400V socket
- 2x32A 230V socket
- Remote control switch
- Arc force regulation indicator
- Welding current regulation indicator

### Options

- Site tow trailer
- Road tow trailer