


**GASOLINE ENGINE SPEED  
3400 r.p.m.**



**HONDA**



**3400  
RPM**



LWA  
2000/14/CE

**NOISE  
level**



**AIR  
cooled**



**GASOLINE**



**SINGLE  
phase**



## GW 3/175

Code **WE17-3M00**

### General features

Noise level	98 Lwa
Dimensions (L. x W. x H.)	560 x 440 x 420 mm
Weight	50 kg
Fuel tank	3,8 lt
Average operating hours	2h ~

### Distribution panel

- 2x16A 230V CEE socket
- Basic/Cellulosic selector
- Welding socket: Positive pole (+)
- Welding socket: Negative pole (-)
- Welding current selector

### Options

- Site tow trailer       Road tow trailer

The company reserves the right to modify the technical specifications, items and design without notice.

The images of the products are indicative for illustrative purposes only.

### Engine

Make/Type	HONDA GX200
Number of cylinders	1
Power	7.2 HP
Engine speed	3400 r.p.m.
Cooling	Air
Fuel	Unleaded gasoline

### Welder

Striking voltage basic	74V
Striking voltage cellulosic	90V
Rated output at 60% duty cycle	165A - 24V
Welding output current max	175A
Range of control	40 - 175A
Electrodes diameter	4mm

### Auxiliary power

Source type	Synchronous alternator
Single phase power	3 kVA
Voltage	230V a.c.
Frequency	50/60Hz
Insulation class	H
Mechanical protection	IP23