



Operation: **ENGINE POWERED** fuel tank capacity 220 litres **Kubota Z482**



ENGINE POWERED Line













FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower 8,5 m, 340° rotatable
- Standard light sensor for machine power on and off
- Galvanized metalworks
- 80 µm powder coating
- Very compact dimensions, up to 22 units per truck
- Central lifting eye longitudinal and transversal forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- · Digital control panel and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Fully bunded tank, 110%
- Certified wind stability up tp 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization













Dimensions & weight	Dimensions min (mm)					Dimensions max(mm)					Total weight (kg)			
Dilliciisiolis & Weight	1200x1200x2560 (LxWxH)					2390x2390x8500 (LxWxH)				101	1013			
Floodlights	Туре		Power (each)			Floodlights numb			Options			Illuminated area (sqm)		
	Led		160W			6			Timer		4200			
Mast	Lifting method		Max Height			Max Wind Speed			Rotation					
	Hydraulic	8	8,5 m			110 km/h			340°					
Alternator	Model		Frequency (Hz)		Insulation class		Degree of protection		Single phase voltage		se voltage	Auxiliary outlets		
	Synchronous		50		Н		IP 23		3,5kVA - 230V		30V	1,2 kVA		
Engine	Model	Fuel		r.p.m.		Tank capacity (I)		Consumption (I/h		/h)) Running time		Noise level dB(A) at 7m	
	Kubota Z482*	Diese	el	1500		220		0,55			400 h		65	

^{*} May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used

