




LED TECHNOLOGY
3300 sqm
Illuminated area

- 
Road maintenance
- 
Security
- 
Outdoor show
- 
Special events
- 
Military applications
- 
Emergency

PLUG-IN Line





Operation: **POWER**
Inlet plug 32A - 230V
Outlet socket 32A - 230V

X-BOX
MANUAL
4x160W LED - 8M

T-ZERO PRO

X-BOX MANUAL

4x160W LED - 8M

T-ZERO PRO



FEATURES

- Telescopic galvanized sections
- 4x160W high efficiency LED heads
- On/off switch to light up the led heads
- Multi-directionally adjustable and tiltable by hands floodlights
- Guided main coiled cable to avoid damage during tower operation
- **Manual winch with automatic brake system**
- Max height 8 meters
- Minimum height when complete close 2,5mt
- Simple, rugged machine design and layout
- Galvanized metalwork after 80 µm industrial powder coated
- **Compact dimensions**
- Assembled on base
- 1150x1150mm base dimensions
- Sides forklift pockets
- Only one front opening door
- **Possibility to link to others towers**
- **Stackable**
- Complete with stabilizers
- 230V inlet plug
- 230V outlet socket

ZERO emissions	ZERO fuel costs	ZERO noise	MINIMAL sevice
STACKABLE	LINKABLE TOWERS	3300 sqm illuminated area	Complete SILENCE on work time 8 HOURS A DAY 7 DAYS A WEEK
			22 units per truck VERY COMPACT dimensions

Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)
		1150x1150x2500 (LxWxH)		2350x2350x8000 (LxWxH)	
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)
	Led	160W	4	65	3300
Mast	Lifting method	Max Height	Max Wind Speed	Safety brake	
	Manual	8 m	110 km/h	Mechanical and included in the winch	
Input&output	Inlet plug		Outlet socket		
	32A - 230V		32A - 230V		