



Lighting Towers



LED TECHNOLOGY

**2600 sqm**  
Illuminated area

Patented mast  
emergency system

**PLUG-IN** Line

- Rail maintenance
- Road maintenance
- Security
- Outdoor show
- Special events
- Military applications
- Emergency



Operation: **POWER**  
**Inlet plug 32A - 230V**  
**Outlet socket 32A - 230V**

**X-CHAIN**  
ANTI-GLARE  
4x150W LED - 7M

**T-ZERO PRO**

## X-CHAIN ANTI-GLARE 4x150W LED - 7M

### T-ZERO PRO



### FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 5 sections vertical tower 7meters, 340° rotatable
- **Manual lifting system by winch complete with auto-braking system**
- Galvanized metalworks
- 80 µm powder coating
- **Very compact dimensions for easy handling & transportability, up to 33 units per truck**
- Light weight for improved manoeuvrability
- Central lifting eye forklift pockets for effective handling
- Guided main coiled cable to avoid damage during tower operation
- Circuit breaker for electrical protection against overload
- Certified wind stability up to 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization
- **Patented mast emergency brake which prevents the falling of the mast in case of cable failure**
- Winch cover
- Top electrical box protection cover
- 2 Retractable galvanized handles
- **Light Sensor as standard feature**
- Bolted Central lifting eye



The first lighting tower in the market that has a patented mast emergency brake system to improve safety of the operators on site  
Registration number: 102017000044431

<b>ZERO emissions</b>	<b>ZERO fuel costs</b>	<b>ZERO noise</b>	<b>MINIMAL sevice</b>
<b>EASY</b> handling & transportability	<b>2600 sqm</b> illuminated area	<b>LINKABLE TOWERS</b>	<b>Complete SILENCE</b> on work time <b>8 HOURS A DAY</b> <b>7 DAYS A WEEK</b>
			<b>33 units per truck</b> <b>VERY COMPACT</b> dimensions

Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)
		1200x850x2100 (LxWxH)		1850x1450x7000 (LxWxH)	
Floodlights	Type	Power (each)	Floodlights number	IP level	illuminated area (sqm)
	Led	150W	4	65	2600
Mast	Lifting method	Max Height	Max Wind Speed	Rotation	Patented mast emergency system
	Manual	7 m	110 km/h	340°	yes
Input&output	Inlet plug	Outlet socket	General	Tower lifting metod	Trailer type
	32A - 230V	32A - 230V		Manual	Hand trolley



**TRIME**® Sales Dept. +39 0382 406 252  
www.trime.it - info@trime.it  
Lighting Towers