


LED TECHNOLOGY

**4400 sqm**  
Illuminated area

**ENGINE POWERED** Line



Operation: **ENGINE POWERED**  
fuel tank capacity 41 litres  
Yanmar L70AE

**X-CITY**

4X320W LED - 7M

# X-CITY

## 4x320W LED - 7M



### FEATURES

- Multi directionally adjustable and tiltable floodlights
- Telescopic vertical mast 7m
- **Manual lifting system by winch complete with auto-breaking system**
- Galvanized metalworks
- 80 µm powder coating
- **Very compact dimensions, up to 22 units per truck**
- Central lifting eye, and forklift pockets for effective handling
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine protection and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Certified wind stability up to 110 km/h
- 4 Height adjustable stabilizers
- On board levels for guidance during stabilization
- Winch cover
- **Site tow trailer with foldable tow bar**

**RUNNING TIME**  
41 litres tank  
**82 h**

**NOISE**   
level 67 dB(A) at 7m

**4400 sqm**  
illuminated area

**22 units**  
per truck

Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)				
	1580x1200x2478 (LxWxH)		1927x2168x7000 (LxWxH)		600				
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)				
	Led	320W	4	67	4400				
Mast	Lifting method		Max Height		Max Wind Speed				
	Manual		7 m		110 km/h				
Generator-double isolation	Model	Rated Output	Rated Frequency	Rated Voltage	Options				
	Linz SP 10M	4,2 kVA	50 Hz	230 V	Site Tow trailer				
Engine	Model	Cylinder	Displacement	Engine speed	Fuel Tank (l)	Consumption (l/h)	Noise level dB(A) at 7m	Average runtime before refueling	Cooling system
	Yanmar L70AE	1	320 cm <sup>3</sup>	3000 rpm	41	0,5	67	82 h	air



**TRIME**® Sales Dept. +39 0382 406 252  
www.trime.it - info@trime.it  
Lighting Towers