



LED TECHNOLOGY

3300 sqm
Illuminated area

PLUG-IN Line



Operation: **POWER**
Inlet plug 16A - 230V
Outlet socket 16A - 230V

X-MAST
4X160W LED - 8,5M
T-ZERO^{PRO}

X-MAST


4x160W LED - 8,5M

T-ZERO^{PRO}



FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 8,5 meters vertical tower, 340° rotatable
- **Manual lifting system by winch complete with auto-braking system**
- Galvanized metalworks
- 80 µm powder coating
- **Very compact dimensions, up to 22 units per truck**
- Sides lifting eyes
- Sites forklift pockets
- Guided main coiled cable to avoid damage during tower operation
- Circuit breaker for electrical protection against overload
- Certified wind stability up to 110 km/h
- 4 extendable & height adjustable stabilizers
- Inlet plug and outlet socket to connect in series more units



Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)
	1100x1100x2650 (LxWxH)		2360x2360x8500 (LxWxH)		430
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)
	Led	160W	4	65	3300
Mast	Lifting method	Max Height	Max Wind Speed		Rotation
	Manual	8,5 m	110 km/h		340°
Input&output	Inlet plug				Outlet socket
	16A - 230V				16A - 230V



TRIME[®] Sales Dept. +39 0382 406 252
www.trime.it - info@trime.it
Lighting Towers