




LED TECHNOLOGY

**5000 sqm**  
Illuminated area

**ENGINE POWERED Line**



Operation: **ENGINE POWERED**  
fuel tank capacity 80 litres  
Kubota Z482

**X-START**  
4x320W - LED - 8M

## X-START 4x320W LED - 8M



### FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections vertical tower 8 m, 340° rotatable
- Galvanized metalworks
- 80 µm powder coating
- Central lifting eye, forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine protection and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Certified wind stability up to 80 km/h
- 5 height adjustable stabilizers
- On board levels for guidance during stabilization

**Cost Effective**

**RUNNING TIME**  
80 litres tank  
145 h  
Low fuel consumption

**NOISE**  
level 65 dB(A) at 7m

**5000 sqm**  
illuminated area

**18 units**  
per truck

Dimensions & weight	Dimensions min (mm)			Dimensions max(mm)		Total weight (kg)		
	1830x1370x2560 (LxWxH)			2320x2570x8000 (LxWxH)		706		
Floodlights	Type	Power (each)		Floodlights number	Illuminated area (sqm)			
	LED	320W		4	5000			
Mast	Lifting method	Max Height		Max Wind Speed		Rotation	Options	
	Manual	8 m		80 km/h		340°	Homologated road trailer	
Alternator	Model	Frequency (Hz)		Insulation class	Degree of protection	Single phase voltage	Auxiliary outlets	
	Synchronous	50		H	IP 23	3,5kVA - 230V	1 kVA	
Engine	Model	Fuel	r.p.m.	Tank capacity (l)		Consumption (l/h)	Running time	Noise level dB(A) at 7m
	Kubota Z482*	Diesel	1500	80		0,55	145 h	65

\* May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used



**TRIME**® Sales Dept. +39 0382 406 252  
www.trime.it - info@trime.it  
Lighting Towers