

# TKS-80 SKID


water  
nebulizer  
**50-150 m**




**90 kVA**

Generator required

R.O.T. SYSTEM



Electric  
Tilting System



Automatic  
Oscillation 340°




Remote control  
50m range

# TKS-80

## SKID

water  
nebulizer  
**50-150 m**



### R.O.T. SYSTEM

- Electric Tilting System
- Automatic oscillation 0 - 340° manual area setting
- Remote control, 50m range programmable function "circle" to start electricmotor-water pump - oscillation with only one button

### FEATURE

- Integrated control panel
- Smart start system
- Emergency stop button
- Separate cabinet
- Water pump 4kW
- Water pressure gauge
- Water safety pressure switch
- Manual water drain system
- Lifting eye
- Forklift pockets
- Stainless steel crown with 36 nozzles
- Galvanized SKID base with forklift pockets

### SAFETY

- Reduce dust for healthy and safe environment
- Safety automatic clutch compliant with HSE norm
- Remote control with full operation
  - start/stop
  - tilt up/down
  - turn left/right/auto

### OPTIONS

- 60 Hz
- External pump for chemicals additives




#### technical data

Electric engine power	kW	<b>45</b>
Inlet plug	-	<b>400V+N+T 50Hz 125A</b>
Fan diameter	mm	<b>1050</b>
Water consumption	l/m	<b>115 - 130</b>
Coverage	m	(still wind conditions)
Max. water throw height	m	<b>30</b>
Water connection	-	<b>UNI 45 or STORZ or CAMLOCK</b>
Min. inlet Water pressure	bar	1.0

#### technical data

Generator required	kVA	<b>90</b>
Water inlet filter	Mesh	<b>60</b>
Y Filter	µm	<b>500</b>
Electric tilting system	-	<b>0 - 35°</b>
Automatic oscillation (working angle settable manually)	-	<b>0 - 340°</b> manual area setting
Dimensions	mm	<b>2238x1493x2389</b>
Weight	Kg	<b>1460</b>



Sales Dept. +39 0382 406 252  
www.trime.it - info@trime.it