designed and created for your needs

X-BOX-HYBRID LITHIUM

4X100W LED - 8.5M

T-ZEROPRO



餌







APPLICATIONS









FEATURES

- Silent operation for 17.5 hrs and an overall running time before first refill of over 2000 hrs.
- On/Off switches one for each lamp
- Multi-directionally adjustable and tiltable by hand floodlights
- 7 galvanised sections Hydraulic lifting system
- Yanmar 2TNV 70 model diesel engine
- Fully bunded
- Battery charger
- Electrical protection from overload and circuit breaker
- Simple, rugged machine design and layout
- 80 μ powder coated
- Galvanised Metalwork
- Compact dimensions
- Guided main coiled cable to avoid damage during tower operation
- Certified wind stability up to 110 km/h
- ♥ 4 stabilisers Central lifting eye base c/w 4 sides forklift pockets

X-BOX-HYBRID LITHIUM

4x100W LED - 8.5M



Dimensions min (mm)	1200x1200x2515 (LxWxH)
Dimensions max (mm)	2390x2390x8500(LxWxH)
Total weight (kg)	1065
Floodlights	
Туре	LED
Power(each)	100W
Floodlights number	4
IP level	65
Illuminated area (sqm)	3000
Mast	
Lifting Method	Hydraulic
Max Height	8.5 m
Max Wind Speed	110 km/h
Safety valve to lower down the mast	Yes
Rotation	340°
Battery Pack	
Туре	Lithium
Batteries number	1
Power Battery pack	25.9 Vdc 200 Ah
Hybrid Mode	
Running time from battery	17.5 hrs
Re-Charging time (with floodlights OFF)	3 h
Complete discharge recharge cycle	20.5 hrs
Hybrid mode consumption	0.08 l/h
Generator	
Model	Linz
Rated Output	3.5 KVA
Outlet socket	N/A - option
Rated frequency	50 Hz
Noise level dB(A) 7 m	0-65
Engine	
Model	Yanmar 2TNV70 liquid cooled
Layout - rpm	2 cylinders 1500 rpm
Fuel tank(I)	160
Fuel consumption	0.55 L/h
Running time before refill	2000 h

