# designed and created for your needs

# X-BOX-HYBRID LITHIUM

6X100W LED - 8.5M

T-ZEROPRO

For a more sustainable and environmentally friendly future

M







## **APPLICATIONS**









### **FEATURES**

- Silent operation for 11.5 hrs and an overall run time before first refill of over 1455 hrs.
- On/Off switches one for each lamp
- Multi-directionally adjustable and tiltable floodlights
- 7 galvanised sections Hydraulic lifting system
- Max height 8.5 m
- Yanmar 2TNV 70 model diesel engine
- 3.5 KVA alternator
- Fully bunded
- 1x Lithium battery
- Battery charger
- Electrical protection from overload and circuit breaker
- Simple, rugged machine design and layout
- Galvanised Metalwork
- Compact dimensions
- Guided main coiled cable to avoid damage during tower operation
- Certified wind stability up to 110 km/h
- ♥ 4 stabilisers Central lifting eye base c/w 4 sides forklift pockets

# X-BOX-HYBRID LITHIUM

6X100W LED - 8.5M



Dimensions & Weight	
Dimensions min (mm)	1200x1200x2515 (LxWxH)
Dimensions max (mm)	2390x2390x8500 (LxWxH)
Total weight (kg)	1100
Floodlights	
Туре	LED
Power(each)	100W
Floodlights number	6
IP level	65
Illuminated area (sqm)	4400
Mast	
Lifting Method	Hydraulic
Max Height	8.5 m
Max Wind Speed	110 km/h
Safety valve to lower down the mast	Yes
Rotation	340°
Battery Pack	
Туре	Lithium
Batteries number	1
Power Battery pack	25.9 Vdc 200 Ah
Hybrid Mode	
Running time from battery	11.5 hrs
Re-Charging time (with floodlights OFF)	3 h
Complete discharge recharge cycle	14.5 hrs
Hybrid mode consumption	0.11 l/h
Generator	
Model	Linz
Rated Output	3.5 KVA
Outlet socket	N/A - option
Rated frequency	50 Hz
Noise level dB(A) 7 m	0-65
Engine	
Model	Yanmar 2TNV70 liquid cooled
Layout - rpm	2 cylinders 1500 rpm
Fuel tank (I)	160
Fuel consumption	0.55 L/h
Running time before refill	1455 h

