



6x160W 48V LED - 8.5M

For a more sustainable and environmentally friendly future

X-BOX

TRIME







6x160W 48V LED - 8.5M





## **APPLICATIONS**











## **FEATURES**

- Multi-directionally adjustable and tiltable floodlights
- Standard light sensor for machine power on and off
- Galvanised metalworks
- Very compact dimensions, up to 22 units per truck
- Central lifting eye, 4 side forklift pockets for effective handling
- Plug & Play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Digital control panel and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button

- 4 extendable & height adjustable stabilisers
- On board levels for guidance during stabilisation

Dimensions & Weight	
Dimensions min (mm)	1200x1200x2560 (LxWxH)
Dimensions max (mm)	2390x2390x8500(LxWxH
Total weight (kg)	1013
Floodlights	<u> </u>
Туре	LED
Power (each)	160W
Floodlights number	6
Options	Timer
Illuminated area (sqm)	7000
Mast	
Lifting Method	Hydraulic
Max Height	8.5 m
Rotation	340°
Max Wind Speed	110 km/h
Alternator	
Model	Synchronous
Frequency (Hz)	50
Insulation class	Н
Degree of protection	IP 23
Single phase voltage	3.5 KVA - 230V
Auxiliary outlets	1.2 KVA
Engine	
Model	Kubota Z482*
Fuel	Diesel
r.p.m.	1500
Tank capacity (I)	220
Consumption (I/h)	0.55
Running time	400 h
Noise level dB(A) at 7m	65

<sup>\*</sup> May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used

