## designed and created for your needs







**Zero Emissions** 



**Zero Fuel** 



**Zero Noise** 



2600 sqm Bright, Instant LED light

linkable towers For a more sustainable and environmentally friendly future














The first lighting tower on the market that has a patented mast emergency brake system to improve safety of the operators on site Registration number: 102017000044431

## **APPLICATIONS**











## **FEATURES**

- Multi-directionally adjustable and tiltable floodlights
- 5 section vertical tower 7 m, 340° rotatable
- Manual lifting system by winch complete with auto-braking system
- Galvanised metalworks
- Very compact dimensions for easy handling & transportability, up to 33 units per truck
- Lightweight for improved manoeuvrability
- Central lifting eye forklift pockets for effective handling
- Guided main coiled cable to avoid damage during tower operation
- Circuit breaker for electrical protection against overload
- Certified wind stability up tp 110 km/h
- 4 extendable & height adjustable stabilisers
- On board levels for guidance during stabilisation
- Patented mast emergency brake which prevents the falling of the mast in case of cable failure
- Winch cover
- Top electrical box protection cover
- 2 Retractable galvanised handles
- Light Sensor as standard feature
- Bolted Central lifting eye

imensions & weight	
Dimensions min (mm)	1200x800x2340(LxWxH)
Dimensions max (mm)	1850x1450x7000 (LxWxH)
Total weight (kg)	318
Floodlights	
Туре	LED
Power (each)	160W
Floodlights number	4
IP level	65
lluminated area (sqm)	4700
1ast	
ifting method	Manual
Max Height	7 m
Max Wind Speed	110 km/h
Rotation	340°
Input&output	
Inlet plug	32A - 230V
Outlet socket	32A - 230V
General	
Tower lifting method	Manual
Frailer type	Hand trolley

